

SPECIFICATION SHEET

JFW MODEL 50T-376

TERMINATION

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-4000 MHz
Impedance	50 Ohms nominal
VSWR	1.10:1 maximum 1.04:1 typical
RF Input Power	2 Watts average
Peak Power	1000 Watts
RF Connector	BNC, N, SMA, TNC or 4.1/9.5 (male or female)
Operating Temperature Range	-20°C to +85°C
Outline Drawing Numbers	092-4072 (50T-376 SMA F) 092-4269 (50T-376 SMA M) 092-7065 (50T-376 N F) 092-4208 (50T-376 N M) 092-7064 (50T-376 TNC F) 092-4444 (50T-376 TNC M) 092-7066 (50T-376 BNC F) 092-6043 (50T-376 BNC M) 092-8688 (50T-376 4.1/9.5 M) 092-8689 (50T-376 4.1/9.5 F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
4324	08/04/2003	A	CLV 08/04/2003	4542	03/30/2004	D	CLV 03/30/2004
4442	01/27/2004	B	SL 01/27/2004	20493	08/23/2011	E	TRS 08/24/2011
4470	02/11/2004	C	CLV 02/11/2004	26961	08/17/2016	F	TRS 08/17/2016