

14 pin DIL VCXO

- Frequency range 38MHz to 640MHz
- LVPECL Output
- Supply Voltage 3.3 VDC
- Phase jitter 0.4ps typical
- Pull range from ± 30 ppm to ± 150 ppm

DESCRIPTION

GPF14 VCXOs are packaged in an industry-standard 14 pin dual-in-line package. Typical phase jitter for GPF series VCXOs is 0.4 ps. Output is LVPECL. Applications include phase lock loop, SONET/ATM, set-top boxes, MPEG, audio/video modulation, video game consoles and HDTV.

SPECIFICATION

Frequency Range:	38.0MHz to 640.0MHz
Supply Voltage:	3.3 VDC $\pm 5\%$
Output Logic:	LVPECL
RMS Period Jitter:	3.0ps typical
Peak to Peak Jitter:	20.0ps typical, 30.0ps maximum
Phase Jitter:	0.4ps typical, 5.0ps maximum
Initial Frequency Accuracy:	Tune to the nominal frequency with $V_c = 1.65 \pm 0.2$ VDC
Output Voltage HIGH (1):	Vdd-1.025V minimum Vdd-0.880V maximum
Output Voltage LOW (0):	Vdd-1.810V minimum Vdd-1.620V maximum ($R_L = 50\Omega$ to Vdd-2V)
Pulling Range:	From ± 30 ppm to ± 150 ppm
Control Voltage Range:	1.65 ± 0.35 Volts
Temperature Stability:	See table
Output Load:	50 Ω into Vdd or Thevenin equiv.
Rise/Fall Times:	0.5ns typ., 0.7ns max. 20% Vdd to 80% Vdd
Duty Cycle:	50% $\pm 5\%$ (Measured at Vdd-1.3V)
Start-up Time:	10ms maximum, 5ms typical
Current Consumption:	75mA maximum at 212.5MHz 80mA maximum at 622.08MHz
Static Discharge Protection:	2kV maximum
Storage Temperature:	-55 $^{\circ}$ to +150 $^{\circ}$ C
Ageing:	± 2 ppm per year maximum
Enable/Disable:	Not implemented - 4 pin package
RoHS Status:	Fully compliant or non-compliant


FREQUENCY STABILITY

Stability Code	Stability \pm ppm	Temp. Range
A	25	0 $^{\circ}$ ~+70 $^{\circ}$ C
B	50	0 $^{\circ}$ ~+70 $^{\circ}$ C
C	100	0 $^{\circ}$ ~+70 $^{\circ}$ C
D	25	-40 $^{\circ}$ ~+85 $^{\circ}$ C
E	50	-40 $^{\circ}$ ~+85 $^{\circ}$ C
F	100	-40 $^{\circ}$ ~+85 $^{\circ}$ C

If non-standard frequency stability is required
Use 'I' followed by stability, i.e. I20 for ± 20 ppm



OUTLINE & DIMENSIONS



PART NUMBERING

