

YA42A1

by Burndy
Catalog ID: YA42A1

Prop 65 Notice

Al Tube Hylug, 1 Hole, 900 KCMIL Al, 1/2 IN Stud, 5.32 IN L, Gray, 303 Index.

UL Listed 90 DEG C, 600 V - 35 KV,Tongue Angle: Straight

Product Details

General

Application	For Aluminum & Copper Conductors
Color Code	Gray
Connector Type	Terminal
Die Index	303
Feature - Barrel Type	Standard
Material	Aluminum
Physical Attribute - Number of Crimps Required	2
Physical Attribute - Number of Holes	1
Physical Attribute - Tongue Type	Standard
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	TERMINALS, HYLUG
Temperature Rating	194
Trade Name	HYLUG™
Type	YA-A
UPC	781810637142
UPC 12 Digit	7818106371422

Dimensions

Dimension - D inch	1.36 in
Dimension - Hole Size inch	0.56 in
Dimension - Hole Size mm	14 mm
Dimension - L Length Overall mm	135 mm
Dimension - Length Overall inch	5.32 in
Dimension - N inch	0.63 in
Dimension - Pad Width inch	2.14 in
Dimension - Strip Length inch	2 7/8
Dimension - Stud Size fraction	1/2
Dimension - Stud Size inch	1/2
Dimension - Z inch	0.71 in
Physical Attribute - Tongue Angle	Straight

Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600
Voltage - Maximum	35000

Conductor Related

Conductor - Copper Str Size	900 Kcmil AL;600 Kcmil CU
Conductor - Copper Str Size Range	900 Kcmil AL-600 Kcmil CU

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	3

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)