



PRODUCT SPECIFICATION

Part Number
PLC760A-WCY04


Details

- Piranha LED
- 7.60 x 7.60 x 7.75mm
- Emitting Color Yellow
- AlInGaP Dice Used

Features

- Flat Lens
- High Luminous Output
- High Current Operation
- RoHS Compliant

Mechanical Dimensions



Notes:

1. Dimensions in millimeters [inch], and tolerance is ± 0.25 [.010] unless otherwise noted.
2. Specifications subject to change without notice





Device Selection Guide

Model Number	Chip	
	Material	Emitting Color
PLC760A-WCY04	AlInGaP	Yellow

Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Rating	Unit
		Y	
Power Dissipation	PAD	300	mW
Continuous Forward Current	IAF	120	mA
Peak Current (duty cycle 1/10, 1KHz)	IPF	100	mA
Reverse Voltage	VR	5	V
Operating Temperature	Topr	-40~+80	°C
Storage Temperature	Tstg	-40~+100	°C
Soldering Conditions	Max. 260°C for 5 sec Max.(3mm from the epoxy body)		

Electrical and Optical Characteristics at Ta=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward Voltage	VF	--	2.5	3.0	V	IF=70mA
Luminous Flux	Iv	6000	8000	--	mlm	
Dominant Wavelength	λD	--	590	--	nm	
Viewing Angle	2θ1/2	--	140	--	deg	
Reverse Current	IR	--	--	10	μA	VR=5V

Luminous Flux Rank Limits (IF = 30mA)

Code	Unit: mlm	
	Min.	Max.
K	6000	7000
L	7000	8000
M	8000	10000
N	10000	12000

Dominant Wavelength Rank Limits (IF = 30mA)

Code	Unit: nm	
	Min.	Max.
Y6	586.5	588
Y7	588	590
Y8	590	592
Y9	592	594

Forward Voltage Rank Limits (IF = 30mA)


Code	Unit: V	
	Min.	Max.
D	2.0	2.2
E	2.2	2.4
F	2.4	2.6
G	2.6	2.8
H	2.8	3.0

Notes:


1. Tolerance of measurement of luminous Flux: $\pm 15\%$
2. Tolerance of measurement of Dominant wavelength: $\pm 2\text{nm}$
3. Tolerance of measurement of forward voltage: $\pm 0.05\text{v}$
4. All data measured by P-tec's test equipment
5. One delivery will include several color rank, VF and Iv ranks of the products.
6. The quantity-ratio of the ranks is decided by P-tec
7. Please confirm with P-tec salesman, if your request differs from standard specifications.

Typical Electrical/Optical Characteristic Curves


- $T_a = 25^\circ\text{C}$ Unless Otherwise Noted






**Fig 1. Forward Current
Vs. Ambient Temperature**



**Fig. 2 Forward Current
Vs. Forward Voltage**



**Fig 3. Relative Intensity
Vs. Forward Current**




Precautions for Use

1. Recommended soldering conditions

1.1. Wave soldering

Basic SPEC. is $\leq 5\text{sec.}$ When 260°C . If temperature is higher, time should be shorter ($+10^{\circ}\text{C} \rightarrow -1\text{sec.}$).



1.2. Recommended Soldering:

Power dissipation of iron should be smaller than 15W and temperature should be controllable.
Soldering temperature should be under 230°C , time 3sec.

2. Static Electricity

2.1 Static electricity or surge voltage damages LEDs.

It is recommended that a wrist band or an anti-electrostatic glove be used when handling the LEDs.

2.2 All devices, equipment and machinery must be properly grounded. It is recommended that measures be taken against surge voltage to the equipment that mounts the LEDs.



Customer Approval Signatures	Approved By	Checked By	Prepared By

[illegible]