


ATB3225-75032CT-T001



| | |
|--------------------------|------------------|
| Application | ISDB-T |
| Cellular Band | |
| Application Grade | Commercial Grade |
| Series | ATB |
| Status | Production |



| Size | |
|--------------|----------------|
| Length(L) | 3.20mm ±0.20mm |
| Width(W) | 2.50mm ±0.20mm |
| Thickness(T) | 2.30mm ±0.10mm |

| Electrical Characteristics | |
|------------------------------|--|
| Characteristic Impedance (Ω) | 75se 50bal |
| Start/Stop Frequency | 5 to 100MHz |
| Insertion Loss [Max.] | 2dB |
| Phase Balance | 180° ± 10° |
| Amplitude Balance | 0dB ± 1dB |
| Return Loss [Min.] | 5dB |
| Further Details | Please refer to the catalog / data sheet |

| Other | |
|-----------------------|--|
| Operating Temp. Range | -25 to 85°C |
| AEC-Q200 | No |
| Packing | Embossed (Plastic)Taping [180mm Reel, Tape width 8mm] |
| Package Quantity | 1000pcs |
| Weight | 0.075g |
| Terminal Shape | |
| Number of Terminal | |
| Further Details | Please refer to the catalog / data sheet |

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

ATB3225-75032CT-T001



Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)