Product data sheet
Characteristics

UTRS213B
Individual meter socket, ringless socket, no bypass, 4 jaws no release, OH, UG, 200 A, up to 600 VAC single phase 3W

Product availability : Stock - Normally stocked in distribution facility

Price** : 212.00 USD



Main

Product or component type	Meter Socket
Meter socket type	Ringless
Hub type	A ACP closing plate

Complementary

Meter socket rated current	200 A
Number of jaws	4 without jaw release
Bypass type	No bypass
Phase	1 phase
[Ue] rated operational voltage	600 V AC
Enclosure material	Steel
Box number	5R
Electrical connection	Lugs 0.5" hex
Service feed location	OH UG
Wiring configuration	3-wire
Device mounting	Surface
AWG gauge	AWG 1/0...350 kcmil 1 aluminium/copper)line AWG 14...AWG 2 1 aluminium/copper)service ground
Depth	111.25 mm (4.38 in)
Width	279.40 mm (11.00 in)
Height	381.00 mm (15.00 in)

Environment

Product certifications	UL listed

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Enclosure Rating	NEMA 3R

Ordering and shipping details

Category	00039 - METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	00785901627661
Returnability	Yes
Country of origin	US

Offer Sustainability

EU RoHS Directive	Will be compliant – Date to be confirmed

Contractual warranty

Warranty	18 months