

## Relay connectors - ST-REL4-KG120/ 1- 1 - 2852777

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Relay connector, fitted with miniature switching relay, contacts (AgNi): Medium to large loads, 2 N/O contacts, 120 V AC/DC input voltage, with light indicator, can be plugged into basic terminal blocks

The illustration shows version ST-REL 4-HW 24/1-1



### Key commercial data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 017918 078669 |
| Weight per Piece (excluding packing) | 46.07 GRM                                                                                               |
| Custom tariff number                 | 85364900                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|        |         |
|--------|---------|
| Width  | 27 mm   |
| Height | 33 mm   |
| Depth  | 66.5 mm |

#### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Ambient temperature (operation)         | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

#### Coil side

|                                           |               |
|-------------------------------------------|---------------|
| Nominal input voltage $U_N$               | 120 V AC/DC   |
| Input voltage range in reference to $U_N$ | 0.85 ... 1.06 |
| Typical input current at $U_N$            | 4 mA          |
| Typical response time                     | 10 ms         |

## Relay connectors - ST-REL4-KG120/ 1- 1 - 2852777

### Technical data

#### Coil side

|                           |                                   |
|---------------------------|-----------------------------------|
| Typical release time      | 10 ms                             |
| Operating voltage display | Yellow LED                        |
| Protective circuit        | Bridge rectifier Bridge rectifier |
|                           | Surge protection Varistor         |

#### Contact side

|                                       |                               |
|---------------------------------------|-------------------------------|
| Contact type                          | Single contact, 2 N/O contact |
| Contact material                      | AgNi                          |
| Maximum switching voltage             | 250 V AC/DC                   |
| Maximum inrush current                | 6 A                           |
| Limiting continuous current           | 5 A                           |
| Interrupting rating (ohmic load) max. | 120 W (at 24 V DC)            |
|                                       | 85 W (at 48 V DC)             |
|                                       | 60 W (at 60 V DC)             |
|                                       | 40 W (at 110 V DC)            |
|                                       | 60 W (at 220 V DC)            |
|                                       | 1250 VA (for 250 V AC)        |

#### General

|                                          |                                               |
|------------------------------------------|-----------------------------------------------|
| Test voltage relay winding/relay contact | 2.5 kV AC (50 Hz, 1 min.)                     |
| Test voltage relay contact/relay contact | 2 kV AC (50 Hz, 1 min.)                       |
| Operating mode                           | 100% operating factor                         |
| Mechanical service life                  | Approx. $5 \times 10^7$ cycles                |
| Standards/regulations                    | DIN VDE 0110b, Gr. C for 250 V DC             |
|                                          | IEC 60255/DIN VDE 0435 (in relevant parts)    |
|                                          | DIN EN 50178/DIN VDE 0160 (in relevant parts) |
|                                          | EN 60730/DIN VDE 0631                         |
|                                          | DIN VDE 0160 (in relevant parts)              |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27371104 |
| eCl@ss 4.1 | 27371104 |
| eCl@ss 5.0 | 27371001 |
| eCl@ss 5.1 | 27371001 |
| eCl@ss 6.0 | 27371001 |
| eCl@ss 7.0 | 27371001 |

## Relay connectors - ST-REL4-KG120/ 1- 1 - 2852777

### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 8.0 | 27371001 |
|------------|----------|

ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000196 |
| ETIM 3.0 | EC000196 |
| ETIM 4.0 | EC000196 |
| ETIM 5.0 | EC000196 |

UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211916 |
| UNSPSC 7.0901 | 39121515 |
| UNSPSC 11     | 39121515 |
| UNSPSC 12.01  | 39121515 |
| UNSPSC 13.2   | 39121515 |

### Approvals

Approvals

---

Approvals

GOST / GOST

---

Ex Approvals

---

Approvals submitted

### Approval details

|                                                                                          |
|------------------------------------------------------------------------------------------|
| GOST  |
|------------------------------------------------------------------------------------------|

|                                                                                          |
|------------------------------------------------------------------------------------------|
| GOST  |
|------------------------------------------------------------------------------------------|

## Relay connectors - ST-REL4-KG120/ 1- 1 - 2852777

### Drawings

Circuit diagram

