

**SPECIFICATION SHEET**

**JFW MODEL 50FHXC-XXX-50**

**FIXED ATTENUATOR**

JFW Industries, Inc.  
Phone: 317-887-1340  
sales@jfwindustries.com  
www.jfwindustries.com

Frequency Range DC-4000 MHz (1-40 dB)  
DC-3000 MHz (41-60 dB)

Impedance 50 Ohms nominal

Attenuation Values 1-60 dB in any 1 dB increment  
(XXX) insert value

VSWR (1-40 dB) 1.15:1 maximum DC-1000 MHz  
1.35:1 maximum 1000-4000 MHz  
(41-60 dB) 1.15:1 maximum DC-1000 MHz  
1.35:1 maximum 1000-3000 MHz

Attenuation Accuracy (1-20 dB)  
± 0.25 dB DC-1000 MHz  
± 0.50 dB 1000-4000 MHz  
(21-30 dB)  
± 0.50 dB DC-1000 MHz  
± 0.75 dB 1000-4000 MHz  
(31-40 dB)  
± 2% DC-2000 MHz  
± 3% 2000-4000 MHz  
(41-60 dB)  
± 2% DC-2000 MHz  
± 3% 2000-3000 MHz

RF Input Power 50 Watts average  
Derate to 25 Watts @ +70° C

Peak Power 1000 Watts

RF Connector BNC, N, SMA, RPT, TNC, 4.1-9.5,  
4.3-10.0 or 7/16  
(RPT = reverse polarity TNC)

Operating Temperature Range -55° C to +100° C

Physical Size See outline drawing 092-6094

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	02/23/2009	O	SMR 02/23/2009	26024	12/14/2015	C	TRS 12/14/2015
25814	10/19/2015	A	TRS 10/19/2015	27539	02/02/2017	D	CLK 02/02/2017
26007	12/14/2015	B	CLK 12/14/2015				