Infrared LED
L1939 series

ϕ300 µm emission spot, no electrode in emission area



Features

- Small emission spot: ϕ300 µm
- Wide directivity
- High reliability, long life

Applications

- Auto-focus
- Optical switches
- Mark sensors

■ Absolute maximum ratings (Ta=25 °C)

Parameter	Symbol	Condition	Value	Unit
Forward current	I_F		100	mA
Reverse voltage	V_R		5	V
Pulse forward current	I_{FP}	Pulse width=10 µs Duty ratio=1 %	1.5	A
Operating temperature	Topr		-30 to +85	°C
Storage temperature	Tstg		-40 to +100 *	°C

* L1939 is guaranteed to resist temperature cycle test of up to 5 cycles.

■ Electrical and optical characteristics (Ta=25 °C)

Parameter	Symbol	Condition	L1939			L1939-04			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	
Peak emission wavelength	λp	I_F=50 mA	870	890	920	870	890	920	nm
Spectral half width	Δλ	I_F=50 mA	-	50	-	-	50	-	nm
Forward voltage	V_F	I_F=50 mA	-	1.4	1.5	-	1.4	1.5	V
Pulse forward voltage	V_{FP}	I_F=1.5 A	-	2.7	3.4	-	2.7	3.4	V
Reverse current	I_R	V_R=5 V	-	-	5	-	-	5	µA
Radiant flux	ϕe	I_F=50 mA	8.0	10.0	-	2.0	2.8	-	mW
Radiant illuminance	P_E	I_F=50 mA	-	0.4	-	-	0.35	-	mW/cm^2
Rise time	tr	I_F=50 mA, 10 to 90 %	-	0.45	0.7	-	0.45	0.7	µs
Fall time	tf	I_F=50 mA, 90 to 10 %	-	0.45	0.7	-	0.45	0.7	µs

SOLID STATE DIVISION

■ Emission spectrum



KLEDB0201EA

■ Radiant flux vs. forward current



KLEDB0146EA

■ Forward current vs. forward voltage



KLEDB0147EA

■ Directivity



Except for reflection ingredient of the base.

KLEDB0148EA

■ Radiant output vs. ambient temperature



KLEDB0145EA

■ Allowable forward current vs. ambient temperature



KLEDB0027EB

■ Allowable forward current vs. duty ratio



KLEDB0149EA

■ Dimensional outlines (unit: mm)

① L1939



② L1939-04



KLEDA0009ED

KLEDA0053EB

HAMAMATSU

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions.
Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2001 Hamamatsu Photonics K.K.

HAMAMATSU PHOTONICS K.K., Solid State Division
1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184, http://www.hamamatsu.com
U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218
Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658
France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10
United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777
North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01
Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

Cat. No. KLED1023E01
Apr. 2001 DN