

Part Number: C2430A

Revision

Date:

1/31/2013

4C/14 19/.0147TC UNSH PVC / PVC**COMMUNICATION & CONTROL CABLE****A. CONSTRUCTION**

Conductor: 14 AWG 19/.0147 TC
Insulation: .032" Wall, Polyvinyl Chloride
Cable Core: 4C @ 6.00" LHL
Jacket: .032" Wall, Polyvinyl Chloride (PVC)

Print Legend: **CAROL (R) 14 AWG -- C2430A-- 75C E60233-8 (UL) CL3**
OR AWM STYLE 2587 -- MADE IN USA

DIAMETERS

.071" nom
.135" nom
.391" nom

B. INDUSTRY APPROVALS

National Electrical Code
UL Standard 13
UL Standard 758

Article 725
Type CL3
AWM Style 2587

C. ELECTRICAL PROPERTIES

Temperature: -20°C to +90°C
Suggested Working Voltage: 600V
Conductor DCR: 2.65 Ohms/M' @ 20°C (Max)
Mutual Capacitance: 28.2 pF/ft @ 1kHz nom

D. COLOR CODE

Cond	COLOR
1	BLACK
2	WHITE
3	RED
4	GREEN

E. CUSTOMER APPROVAL

Signature: _____
Date: _____