



# Rotary indexing table DHTG-65-4-A

Part number: 548077

FESTO



## Data sheet

Feature	Value
Size	65 65
Parallelism of plate	≤0.04 mm
Axial eccentricity of plate	≤0.02 mm
Plate concentricity	≤0.02 mm
Repetition accuracy of swivel angle	≤0.03 deg
Type code	DHTG DHTG
Cushioning	Pneumatic shock absorber, hard characteristic curve, adjustable Pneumatic shock absorber, hard characteristic curve, adjustable
Mounting position	Any Any
Mode of operation	Double-acting
Design	Gear coupling Gear rack/pinion Positively driven motion sequence Gear coupling Gear rack/pinion Positively driven motion sequence
Symbol	00992251
Position sensing	For inductive proximity sensors For inductive proximity sensors
Spacing	4
Operating pressure	4 bar ... 8 bar
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4] Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use) Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress 2 - Moderate corrosion stress
Noise level	≤70 dB(A)
Ambient temperature	5 °C ... 60 °C
Max. axial force static	1000 N
Max. pull-out torque static	100 Nm
Max. radial force static	2000 N
Max. tangential torque static	100 Nm

<b>Feature</b>	<b>Value</b>
Theoretical torque at 6 bar	2.1 Nm
Product weight	1900 g
Type of mounting	Via through-hole and centering sleeve Via through-hole and centering sleeve
Pneumatic connection	Internal thread M5 Internal thread M5
Plate material	Steel, galvanized
Note on materials	RoHS-compliant Free of copper and PTFE Free of copper and PTFE RoHS-compliant
Stops material	Steel, galvanized Steel, galvanized
Cover material	Wrought aluminum alloy Wrought aluminum alloy
Seals material	NBR TPE-U(PU) NBR TPE-U(PU)
Housing material	Wrought aluminum alloy Wrought aluminum alloy