





PIN NO.	PIN ASSIGNMENT
C1	SUPPLY VOLTAGE(VCC)
C2	RESET(RST)
C3	CLOCK(CLK)
C4	RESERVED FOR FUTURE USE(RFU)
C5	GROUND(GND)
C6	PROGRAMMING VOLTAGE(VPP)
C7	I/O
C8	RESERVED FOR FUTURE USE(RFU)



PCB LAYOUT - COMPONENT VIEW



TECHNICAL CHARACTERISTICS

MATERIAL
INSULATOR: LCP
FLAMABILITY RATING: UL94-V0
COLOR: BLACK
CONTACT MATERIAL: COPPER ALLOY
CONTACT TYPE: STAMPED
CONTACT PLATING: SELECTIVE GOLD
SHIELDING: STAINLESS STEEL
QUALITY CLASS: 2500 MATING CYLCES

ENVIRONMENTAL
OPERATING TEMPERATURE: -25°C UP TO +85°C
COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
CURRENT RATING: 1.0A
WORKING VOLTAGE: 15V DC
INSULATION RESISTANCE: >1000 MΩ
WITHSTANDING VOLTAGE: 500 VAC/min
CONTACT RESISTANCE: 30 mΩ max

SOLDERING
JEDEC LEAD FREE REFLOW SOLDERING PROCESS

PACKAGING
TAPE & REEL WITH MYLAR

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = ± 0.3 .XX = ± 0.20		DESCRIPTION: MICRO SIM - HINGE TYPE - 8 PINS WERI PART NO: 693 022 010 811	SIZE A4
G								
F								
E								
D								
C				APPROVAL: RJ	UNIT: MM			
B					SCALE:			
A	29-JUL-14	PDF	AS		SHEET: 1/3			
REV	DATE	FILE	BY		DRAW: AS			

[illegible]