


System connectors - FLKM 50-PA-MELSEC A1S/32-I - 2290339

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE front adapter, for Mitsubishi Electric MELSEC A1S X81

Key commercial data

Packing unit	1 pc
GTIN	 4 017918 057985
Weight per Piece (excluding packing)	75.7 GRM
Custom tariff number	85369010
Country of origin	Germany

Technical data

General

Nominal voltage U_N	24 V AC/DC
Max. permissible current	1 A (per path)
Connection type, connector	Flat-ribbon cable connector in acc. with IEC 60603-13
Number of connectors	1
No. of positions, connector	50
Number of positions	50
Mounting position	any
Standards/regulations	IEC 60664 IEC 60664 A DIN VDE 0110 DIN VDE 0160 (in parts)
Pollution degree	2
Surge voltage category	II

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
---------------------------------	------------------

System connectors - FLKM 50-PA-MELSEC A1S/32-I - 2290339

Technical data

Ambient conditions

Ambient temperature (storage/transport)	-20 °C ... 70 °C
---	------------------

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27242208
eCl@ss 7.0	27242208

ETIM

ETIM 2.0	EC001423
ETIM 3.0	EC001423
ETIM 4.0	EC001423
ETIM 5.0	EC001423

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Approvals

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

System connectors - FLKM 50-PA-MELSEC A1S/32-I - 2290339

Approvals

Approval details

GOST 