

# A General Specifications

## Electrical Capacity (Resistive Load)

**Power Level (silver):** 6A @ 125V AC & 3A @ 250V AC  
 4A @ 30V DC for On-None-On & On-None-Off; 3A @ 30V DC for all other circuits  
**Logic Level (gold):** 0.4VA maximum @ 28V AC/DC maximum (Applicable Range 0.1mA ~ 0.1A @ 20mV ~ 28V)  
**Logic/Power Level (gold over silver):** Combines silver & gold ratings  
 Note: Find additional explanation of dual rating & operating range in Supplement section.

## Other Ratings

**Contact Resistance:** 10 milliohms maximum for silver; 20 milliohms maximum for gold  
**Insulation Resistance:** 1,000 megohms minimum @ 500V DC  
**Dielectric Strength:** 1,000V AC minimum between contacts for 1 minute minimum;  
 1,500V AC minimum between contacts and case for 1 minute minimum  
**Mechanical Life:** 100,000 operations minimum; 50,000 operations minimum for flat, locking & splashproof devices  
**Electrical Life:** 25,000 operations minimum for silver; 50,000 operations minimum for gold;  
 50,000 operations minimum for silver at 3A @ 125V AC  
**Angle of Throw:** 25°

## Materials & Finishes

**Toggle:** Brass with chrome plating  
**Bushing:** Brass with nickel plating  
**Case:** Diallyl phthalate resin (UL94V-0)  
**Movable Contactor:** Phosphor bronze with silver or gold plating  
**Movable Contacts:** Silver alloy (code W); copper with gold plating (code G); or silver alloy with gold plating (code A)  
**Stationary Contacts:** Silver with silver plating (code W); copper or brass with gold plating (code G);  
 or silver with gold plating (code A)  
**Terminals:** Copper or brass with silver plating; or copper or brass with gold plating

**Frame:** Stainless steel  
**Support Bracket:** Brass with tin plating

## Environmental Data

**Operating Temp Range:** -30°C through +85°C (-22°F through +185°F)  
**Humidity:** 90 ~ 95% humidity for 96 hours @ 40°C (104°F)  
**Vibration:** 10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours  
**Shock:** 50G (490m/s<sup>2</sup>) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)  
**Sealing:** Splashproof bushing options B3, D3, D8, L3, & L8, which have o-rings inside & outside the bushing, meet IP67 of IEC60529 Standards.

## Installation

**Mounting Torque:** 3.0Nm (26.55 lb•in) double nut for large bushing;  
 1.5Nm (13 lb•in) double nut & 0.7Nm (6 lb•in) single nut for all other bushings

## Processing

**Soldering:** Wave Soldering (PC version) for Gold: See Profile A in Supplement section.  
 Manual Soldering for Gold: See Profile A in Supplement section.  
 Wave Soldering (PC version) for Silver: See Profile B in Supplement section.  
 Manual Soldering for Silver: See Profile B in Supplement section.  
 Note: Lever must be in OFF (center) position while soldering.  
**Cleaning:** These devices are not process sealed. Hand clean locally using alcohol based solution.

## Standards & Certifications

**Flammability Standards:** UL94V-0 for case  
**UL:** File No. E44145 - Recognized only when ordered with marking on switch.  
 Add "/U" or "/CUL" before dash in part number to order UL recognized switch.  
 All models recognized at 6A @ 125V AC, 3A @ 250V AC or 0.4VA maximum @ 28V DC maximum.  
**CSA:** File No. 023535\_0\_000 - Certified only when ordered with marking on switch.  
 Add "/C" before dash in part number to order CSA certified switch.  
 All models certified at 6A @ 125V AC or 3A @ 250V AC or 0.4VA maximum @ 28V maximum.

# Distinctive Characteristics

Antirotation design, standard on noncylindrical levers, mates toggle and bushing; bottom of toggle has two flattened sides which fit into a complementary opening inside bushing.

Antijamming design protects contacts from damage due to excessive downward force on actuator.

High torque bushing construction prevents rotation or separation from frame during installation.

High insulating barriers increase isolation of circuits in multipole devices and provide added protection to contact points.


Molded diallyl phthalate case has a UL flammability rating of 94V-0.

Epoxy sealed terminals prevent entry of solder flux and other contaminants.



Prominent external insulating barriers increase insulation resistance and dielectric strength.

Interlocked actuator block, lever, and interior guide prevent switch failure due to biased lever movement.

Clinching of frame to case well above base and terminals provides 1,500V dielectric strength.




Actual Size




Bushing Mount

Page A48



Bracket PC Mount

Page A60



Angle PC Mount

Page A66

A  
Toggles

Rockers

Pushbuttons

Programmable  
Illuminated PB

Keylocks

Rotaries

Slides

Tactiles

Tilt



Touch

Indicators

Accessories

Supplement

TYPICAL SWITCH ORDERING EXAMPLE



DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

M2012S2A2G40






IMPORTANT:

Switches are supplied without UL, cULus & CSA marking unless specified. **UL, cULus & CSA recognized only when ordered with marking on the switch.** Specific models, ratings, & ordering instructions are noted on General Specifications page.









### POLES & CIRCUITS

| Pole | Model   | Toggle Position<br>( ) = Momentary                                                        |                                                                                             |                                                                                         | Connected Terminals                                                                       |                                                                                             |                                                                                         | Throw & Schematics                                                                                                              |
|------|---------|-------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
|      |         | Down<br> | Center<br> | Up<br> | Down<br> | Center<br> | Up<br> |                                                                                                                                 |
| SP   | * M2012 | ON                                                                                        | NONE                                                                                        | ON                                                                                      |                                                                                           |                                                                                             |                                                                                         | Note: Terminal numbers are not actually on the switch.<br>* Reverse circuits available for vertical mount SP & DP upon request. |
|      | M2013   | ON                                                                                        | OFF                                                                                         | ON                                                                                      |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |
|      | M2015   | ON                                                                                        | NONE                                                                                        | (ON)                                                                                    | 2-3                                                                                       | OPEN                                                                                        | 2-1                                                                                     |                                                                                                                                 |
|      | * M2018 | (ON)                                                                                      | OFF                                                                                         | (ON)                                                                                    |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |
|      | M2019   | ON                                                                                        | OFF                                                                                         | (ON)                                                                                    |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |
| DP   | * M2022 | ON                                                                                        | NONE                                                                                        | ON                                                                                      |                                                                                           |                                                                                             |                                                                                         |                                              |
|      | M2023   | ON                                                                                        | OFF                                                                                         | ON                                                                                      |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |
|      | M2025   | ON                                                                                        | NONE                                                                                        | (ON)                                                                                    | 2-3 5-6                                                                                   | OPEN                                                                                        | 2-1 5-4                                                                                 |                                                                                                                                 |
|      | * M2028 | (ON)                                                                                      | OFF                                                                                         | (ON)                                                                                    |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |
|      | M2029   | ON                                                                                        | OFF                                                                                         | (ON)                                                                                    |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |
| 3P   | M2032   | ON                                                                                        | NONE                                                                                        | ON                                                                                      |                                                                                           |                                                                                             |                                                                                         |                                              |
|      | M2033   | ON                                                                                        | OFF                                                                                         | ON                                                                                      |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |
|      | M2035   | ON                                                                                        | NONE                                                                                        | (ON)                                                                                    | 2-3 5-6 8-9                                                                               | OPEN                                                                                        | 2-1 5-4 8-7                                                                             |                                                                                                                                 |
|      | M2038   | (ON)                                                                                      | OFF                                                                                         | (ON)                                                                                    |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |
|      | M2039   | ON                                                                                        | OFF                                                                                         | (ON)                                                                                    |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |
| 4P   | M2042   | ON                                                                                        | NONE                                                                                        | ON                                                                                      |                                                                                           |                                                                                             |                                                                                         |                                            |
|      | M2043   | ON                                                                                        | OFF                                                                                         | ON                                                                                      |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |
|      | M2045   | ON                                                                                        | NONE                                                                                        | (ON)                                                                                    | 2-3 5-6 8-9 11-12                                                                         | OPEN                                                                                        | 2-1 5-4 8-7 11-10                                                                       |                                                                                                                                 |
|      | M2048   | (ON)                                                                                      | OFF                                                                                         | (ON)                                                                                    |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |
|      | M2049   | ON                                                                                        | OFF                                                                                         | (ON)                                                                                    |                                                                                           |                                                                                             |                                                                                         |                                                                                                                                 |


### For 3 Throw (3-On)

### Connected Terminals & Schematics

| Pole | Model | Down | Center | Up   | Down                                                                                | Center                                                                               | Up                                                                                    |
|------|-------|------|--------|------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| SP   | M2024 | ON   | ON     | ON   |  |  |  |
|      | M2026 | (ON) | ON     | (ON) |                                                                                     |                                                                                      |                                                                                       |
|      | M2027 | ON   | ON     | (ON) |                                                                                     |                                                                                      |                                                                                       |
| DP   | M2044 | ON   | ON     | ON   |  |  |  |
|      | M2046 | (ON) | ON     | (ON) |                                                                                     |                                                                                      |                                                                                       |
|      | M2047 | ON   | ON     | (ON) |                                                                                     |                                                                                      |                                                                                       |


The SP3T model utilizes a double pole base.

External connection must be made during field installation.



The DP3T model utilizes a four pole base.

External connection must be made during field installation.




## SMALL TOGGLES


### Important:

Toggle length changes based on bushing selected. All illustrations are shown with .350" (8.9mm) long bushing. When using a .280" (7.1mm) long bushing, toggle length increases .070" (1.78mm).


### S .413" (10.5mm) Bat




### S2 .200" (5.08mm) Bat




### S3 .256" (6.5mm) Bat



### E .450" (11.4mm) Flatted





### E2 .256" (6.5mm) Flatted





**Standard Material & Finish:** Brass with Bright Chrome  
Contact factory for optional finishes.

## SMALL BUSHINGS

### A2 .280" (7.1mm) Smooth with Keyway





### S2 .350" (8.9mm) Smooth with Keyway





When using this bushing, toggle length is increased by .070" (1.78mm).

### A1 .280" (7.1mm) Threaded with Keyway



### S1 .350" (8.9mm) Threaded with Keyway




When using this bushing, toggle length is increased by .070" (1.78mm). Maximum Panel Thickness with Standard Hardware: .031" (0.8mm)


Maximum Panel Thickness with Standard Hardware: .102" (2.6mm)

### Panel Cutouts

For A2, S2, A1 or S1 Bushing with Keyway



For A1 or S1 Bushing with Locking Ring



### Standard Hardware:

- 2 Hex Nuts (AT513H)
- 1 Lockwasher (AT509)
- 1 Locking Ring (AT507H)


For dimensions, see Accessories & Hardware section.

### LOCKING LEVER & BUSHING


**LL2**

Smooth with Keyway

Locking Mechanism



on-none-on




2 positions lock

on-none-(on)




1 position locks

on-off-(on)  
on-on-(on)




2 positions lock

on-off-on  
on-on-on




3 positions lock

(on)-off-(on)  
(on)-on-(on)



1 position locks

**No Code**



Cap for Locking Lever

Supplied with Cap AT427  
Material & Finish:

Brass with Nickel Plating

Lever Material & Finish:

Brass with Chrome Plating

Color Codes for Optional  
Anodized Aluminum Caps

**A**

Black

**C**

Red

**G**

Blue

### CONTACT MATERIALS & RATINGS

**W**

Silver over Silver

Power Level

6A @ 125V AC & 3A @ 250V AC

**G**

Gold over Brass or Copper

Logic Level

0.4VA maximum @ 28V AC/DC maximum

Note: See Supplement section to find complete explanation of operating range.

**A**

Gold over Silver

Power Level  
or Logic Level



6A @ 125V AC  
or 0.4VA maximum @ 28V AC/DC maximum

Note: This dual rated option is suitable when two or more identical switches are used in logic and in power circuits within the same application. See Supplement section to find complete explanation of dual rating and operating range.


### TERMINALS

**30**


.150" (3.81mm)  
Right Angle PC (1-3 Pole)



Single Pole





Double Pole



Three Pole

**32**



Right Angle PCB  
with Reverse Circuit  
(1 Pole & 0.4VA Rating Only)




Terminal dimensions are shown on the Typical Switch Dimensions pages which follow.

## TERMINALS (Continued)


### 40 .150" (3.81mm) Vertical PC (1-4 Pole)




Single Pole



Double Pole





Three Pole




Four Pole


### 45 .100" (2.54mm) Vertical PC (1-4 Pole)




Single Pole



Double Pole



Three Pole




Four Pole

Terminal dimensions are shown on the Typical Switch Dimensions pages which follow.

## OPTIONAL CAPS & CAP COLORS


### B AT415 for S Bat Toggle

Material:  
Polyethylene



### C AT444 Conical Cap for S Bat Toggle

Material:  
Polyethylene





### Colors Available



|                |                 |
|----------------|-----------------|
| <b>A</b> Black | <b>E</b> Yellow |
| <b>B</b> White | <b>F</b> Green  |
| <b>C</b> Red   | <b>G</b> Blue   |

## STANDARD HARDWARE



**AT513H for Inch**  
**AT513M for Metric**  
**Hex Nut (2 per switch)**  
Brass/Nickel



**AT507H for Inch**  
**AT507M for Metric**  
**Locking Ring (1 per switch)**  
Steel with Zinc/Chromate






**AT509**  
**Lockwasher (1 per switch, none with splashproof)**  
Steel with Zinc/Chromate



### TYPICAL SWITCH DIMENSIONS

#### .150" (3.81mm) Right Angle PC




#### Single Pole



M2012S2A2G30

#### .150" (3.81mm) Right Angle PC





#### Double Pole



M2022S2A2G30

#### .150" (3.81mm) Right Angle PC




#### Three Pole



M2032S2A2G30

#### Right Angle PCB

#### Single Pole • Reverse Circuit





M2012S2A2G32

## TYPICAL SWITCH DIMENSIONS

### Single Pole




.150" (3.81mm) Vertical PC



M2012S2A2G40

### Double Pole



.150" (3.81mm) Vertical PC



M2022S2A2G40

### Three Pole



.150" (3.81mm) Vertical PC



M2032S2A2G40

### Four Pole

.150" (3.81mm) Vertical PC



M2042S2A2G40

A Toggles

Rockers

Pushbuttons

Illuminated PB

Programmable

Keylocks

Rotaries

Slides

Tactiles

Tilt

Touch

Indicators




Accessories

Supplement

### TYPICAL SWITCH DIMENSIONS

#### .100" (2.54mm) Vertical PC




#### Single Pole



M2012S2A2G45

#### .100" (2.54mm) Vertical PC




#### Double Pole



M2022S2A2G45

#### .100" (2.54mm) Vertical PC




#### Three Pole



M2032S2A2G45

#### .100" (2.54mm) Vertical PC

#### Four Pole



M2042S2A2G45