Patch panels - FOC-FR19:1U-2OS12-LCD12-OM1 - 1419973

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Patch panels, type: 19" rack patch module, degree of protection: IP20, number of positions: 24, material: Aluminum alloy, color: gray

Your advantages

- Fast and reliable cabling, thanks to clear connections on the front
- Plug & Play
- Compact design with MT ferrule

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	4 055626 198903
GTIN	4055626198903

Technical data

Mechanical characteristics

Number of positions	24
Number of slots	12
Locking type	Push Pull
Fiber type	GOF
Insertion/withdrawal cycles	≥ 500 (In the event of repeated cleaning)
Type of cable	Fan out
Color	gray
Mounting type	Screw mounting
Degree of protection	IP20
Type	1 HE
No. of cable outlets	0

Ambient conditions

Ambient temperature (operation)	-10 °C ... 60 °C (IEC 61300-2-22)

Patch panels - FOC-FR19:1U-2OS12-LCD12-OM1 - 1419973

Technical data

Ambient conditions

Degree of protection	IP20
	IP20

Material data

Flammability rating according to UL 94	V0
Housing material	Aluminum alloy
Housing surface material	Powder-coated, gray
Outer sheath, material	LSFH
Ferrule material	Zirconia ceramics
Depth	220 mm
Height	132 mm

Standards and Regulations

Halogen-free	complying with IEC 60754-1/2
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”

Phoenix Contact 2019 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com