Product data sheet
Characteristics

HU362AWH
Safety switch, heavy duty, non fusible, 60A, 600 VAC/VDC, 3 poles, 60 hp, NEMA 12K, hubbellock receptacle

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 2,310.00 USD



Main

Product	Receptacle Switch
For Use With	Plug SD12781 Hubbellock
Disconnect Type	Non-fusible disconnect switch
Phase	3 phase
Number of Poles	3
Current rating	60 A
Voltage Rating	600 V AC 250 V DC
Enclosure Rating NEMA 3R	NEMA 12K
Maximum Horse Power Rating	50 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 60 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 10 hp 250 V at DC conforming to NEC 430.52

Complementary

Mounting Type	Surface
Electrical Connection	Receptacle
Wire Configuration	4-wire
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Tightening torque	45 lbf.in (5.08 N.m) (AWG 6...AWG 4) 40 lbf.in (4.52 N.m) (AWG 8) 35 lbf.in (3.95 N.m) (AWG 14...AWG 10)
Depth	7 in (177.80 mm)
Width	10.5 in (266.70 mm)
Height	16.5 in (419.10 mm)

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Certifications	UL Listed

Ordering and shipping details

Category	00119 - H&HU SW,W/HUBBELL RECPT-WH
Discount Schedule	DE1
GTIN	00785901505068
Nbr. of units in pkg.	1
Package weight(Lbs)	20.01 lb(US) (9.08 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	31.44 in (79.849 cm)
Package 1 width	7.37 in (18.732 cm)
Package 1 Length	13.44 in (34.129 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months