


# Servo motor EMMS-AS-55-S-LS-RR

Part number: 1569740

FESTO



## Data sheet

Feature	Value
Number of pole pairs	4
Type code	EMMS-AS
Rotor position sensor	Resolver
Rotor position sensor interface	SIN/COS analog signals
Rotor position sensor measuring principle	Inductive
Temperature monitoring	PTC resistor
Max. rotational speed	9800 1/min
Nominal rotary speed	7400 1/min
Insulation protection class	F
Motor constants	0.406 Nm/A
Nominal operating voltage DC	360 V
Motor nominal power	261 W
DC nominal voltage	360 V
Motor nominal current	0.83 A
Phase-phase winding resistance	20.9 Ohm
Winding inductance phase-phase	15.6 mH
Type of winding switch	Star inside
Peak current	4.3 A
Voltage constant, phase-to-phase	26 mVmin
Rating class according to EN 60034-1	S1
CE marking (see declaration of conformity)	As per EU EMC directive As per EU low voltage directive
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
Storage temperature	-20 °C ... 60 °C
Relative air humidity	0 - 90 %
Degree of protection	IP54
Ambient temperature	-10 °C ... 40 °C
Certification	RCM compliance mark c UL us - Recognized (OL)
Total output inertia moment	0.13 kgcm <sup>2</sup>
Nominal torque	0.34 Nm
Peak torque	1.65 Nm
Stall torque	0.49 Nm
Permissible axial shaft load	75 N
Permissible radial shaft load	140 N
MTTF, subcomponent	80 years, rotor position sensor

<b>Feature</b>	<b>Value</b>
MTTFd, subcomponent	160 years, rotor position sensor
Product weight	1200 g
Electrical connection technology	Plug
Note on materials	RoHS-compliant
Conforms to standard	IEC 60034