- **Organization**
  TM124MBK36F . . . 1 048 576 × 36
  TM248NBK36F . . . 2 097 152 × 36
- **Single 5-V Power Supply (±10% Tolerance)**
- **72-Pin Single-In-Line Memory Module (SIMM) for Use With Socket**
- **TM124MBK36F – Utilizes Two 16-Megabit and One 4-Megabit DRAMs in Plastic Small-Outline J-Lead (SOJ) Packages**
- **TM248NBK36F – Utilizes Four 16-Megabit and Two 4-Megabit DRAMs in Plastic Small-Outline J-Lead (SOJ) Packages**
- **Long Refresh Period . . . 16 ms (1024 Cycles)**
- **All Inputs, Outputs, Clocks Fully TTL Compatible**
- **3-State Output**
- **Common $\overline{CAS}$ Control for Nine Common Data-In and Data-Out Lines in Four Blocks**
- **Enhanced Page-Mode Operation With $\overline{CAS}$-Before-$\overline{RAS}$ (CBR), $\overline{RAS}$-Only, and Hidden Refresh**
- **Presence Detect**
- **Performance Ranges:**

	ACCESS TIME t_{RAC} (MAX)	ACCESS TIME t_{AA} (MAX)	ACCESS TIME t_{CAC} (MAX)	READ OR WRITE CYCLE (MIN)
'124MBK36F-60	60 ns	30 ns	15 ns	110 ns
'124MBK36F-70	70 ns	35 ns	18 ns	130 ns
'124MBK36F-80	80 ns	40 ns	20 ns	150 ns
'248NBK36F-60	60 ns	30 ns	15 ns	110 ns
'248NBK36F-70	70 ns	35 ns	18 ns	130 ns
'248NBK36F-80	80 ns	40 ns	20 ns	150 ns

- **Low Power Dissipation**
- **Operating Free-Air Temperature Range: 0°C to 70°C**
- **Gold-Tabbed Versions Available:†**
  - **TM124MBK36F**
  - **TM248NBK36F**
- **Tin-Lead (Solder) Tabbed Versions Available:**
  - **TM124MBK36U**
  - **TM248NBK36U**

description

TM124MBK36F

The TM124MBK36F is a 4-MByte dynamic random-access memory (DRAM) organized as four times 1048576 × 9 in a 72-pin single-in-line memory module (SIMM). The SIMM is composed of two TMS418160DZ, 1 048 576 × 16-bit dynamic RAMs, each in a 42-lead plastic small-outline J-lead (SOJ) package and one TMS44460DJ, 1048576 × 4-bit DRAM in a 24/26-lead plastic small-outline J-lead (SOJ) package mounted on a substrate with decoupling capacitors. The TMS418160DZ and TMS44460DJ are described in the TMS418160 and TMS44460 data sheets, respectively. The TM124MBK36F SIMM is available in the single-sided BK leadless module for use with sockets.

TM248NBK36F

The TM248NBK36F is an 8-MByte DRAM organized as four times 2097152 × 9 in a 72-pin single-in-line memory module (SIMM). The SIMM is composed of four TMS418160DZ, 1 048 576 × 16-bit dynamic RAMs, each in a 42-lead plastic small-outline J-lead (SOJ) package and two TMS44460DJ, 1048576 × 4-bit DRAMs, each in a 24/26-lead plastic small-outline (SOJ) package mounted on a substrate with decoupling capacitors. The TMS418160DZ and TMS44460DJ are described in the TMS418160 and TMS44460 data sheets, respectively. The TM248NBK36F SIMM is available in the double-sided BK leadless module for use with sockets.

operation

The TM124MBK36F operates as two TMS418160DZs and one TMS44460DJ connected as shown in the functional block diagram and NO TAG. The TM248NBK36F operates as four TMS418160DZs and two TMS44460DJs connected as shown in the functional block diagram and NO TAG. The common I/O feature dictates the use of early write cycles to prevent contention on D and Q.


† Part numbers in this data sheet are for the gold-tabbed version; the information applies to both gold-tabbed and solder-tabbed versions.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1995, Texas Instruments Incorporated

BK SINGLE-IN-LINE MEMORY MODULE

(TOP VIEW)




TM124MBK36F

(SIDE VIEW)



TM248NBK36F

(SIDE VIEW)



PIN NOMENCLATURE	
A0–A9	Address Inputs
$\overline{CAS0}$–$\overline{CAS3}$	Column-Address Strobe
DQ0–DQ35	Data In/Data Out
NC	No Connection
PD1– PD4	Presence Detects
$\overline{RAS0}$–$\overline{RAS3}$	Row-Address Strobe
V_{CC}	5-V Supply
V_{SS}	Ground
$\overline{W}$	Write Enable

PRESENCE DETECT					
SIGNAL (PIN)		PD1 (67)	PD2 (68)	PD3 (69)	PD4 (70)
TM124MBK36F	80 ns	V_{SS}	V_{SS}	NC	V_{SS}
	70 ns	V_{SS}	V_{SS}	V_{SS}	NC
	60 ns	V_{SS}	V_{SS}	NC	NC
TM248NBK36F	80 ns	NC	NC	NC	V_{SS}
	70 ns	NC	NC	V_{SS}	NC
	60 ns	NC	NC	NC	NC

Table 1. Connection Table


DATA BLOCK	$\overline{\text{RAS}}$x		$\overline{\text{CAS}}$x
	SIDE 1	SIDE 2†	
DQ0–DQ7	$\overline{\text{RAS0}}$	$\overline{\text{RAS1}}$	$\overline{\text{CAS0}}$
DQ8	$\overline{\text{RAS2}}$	$\overline{\text{RAS3}}$	$\overline{\text{CAS0}}$
DQ9–DQ16	$\overline{\text{RAS0}}$	$\overline{\text{RAS1}}$	$\overline{\text{CAS1}}$
DQ17	$\overline{\text{RAS2}}$	$\overline{\text{RAS3}}$	$\overline{\text{CAS1}}$
DQ18–DQ25	$\overline{\text{RAS2}}$	$\overline{\text{RAS3}}$	$\overline{\text{CAS2}}$
DQ26	$\overline{\text{RAS2}}$	$\overline{\text{RAS3}}$	$\overline{\text{CAS2}}$
DQ27–DQ34	$\overline{\text{RAS2}}$	$\overline{\text{RAS3}}$	$\overline{\text{CAS3}}$
DQ35	$\overline{\text{RAS2}}$	$\overline{\text{RAS3}}$	$\overline{\text{CAS3}}$

† Side 2 applies to the TM248NBK36F only.


single in-line memory module and components

PC substrate: 1,27 ± 0,1 mm (0.05 inch) nominal thickness; 0.005 inch/inch maximum warpage
Bypass capacitors: Multilayer ceramic
Contact area for TM124MBK36F and TM248NBK36F: Nickel plate and gold plate over copper
Contact area for TM124MBK36U and TM248NBK36U: Nickel plate and tin/lead over copper

functional block diagram [TM124MBK36F and TM248NBK36F, side 1]



functional block diagram [TM248NBK36F, side 2]



absolute maximum ratings over operating free-air temperature (unless otherwise noted)†

Supply voltage range, V_{CC} (see Note 1) . . . . . – 1 V to 7 V
Voltage range on any pin (see Note 1) . . . . . – 1 V to 7 V
Short-circuit output current . . . . . 50 mA
Power dissipation TM124MBK36F, TM124MBK36U . . . . . 3 W
TM248NBK36F, TM248NBK36U . . . . . 6 W
Operating free-air temperature range, T_A . . . . . 0°C to 70°C
Storage temperature range, T_{stg} . . . . . – 55°C to 125°C

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: All voltage values are with respect to V_{SS}.

recommended operating conditions

		MIN	NOM	MAX	UNIT
V_{CC}	Supply voltage	4.5	5	5.5	V
V_{IH}	High-level input voltage	2.4		6.5	V
V_{IL}	Low-level input voltage (see Note 2)	– 1		0.8	V
T_A	Operating free-air temperature	0		70	°C

NOTE 2: The algebraic convention, where the more negative (less positive) limit is designated as minimum, is used for logic-voltage levels only.

electrical characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted)

PARAMETER		TEST CONDITIONS	'124MBK36F-60		'124MBK36F-70		'124MBK36F-80		UNIT
			MIN	MAX	MIN	MAX	MIN	MAX	
V_{OH}	High-level output voltage	I_{OH} = – 5 mA	2.4		2.4		2.4		V
V_{OL}	Low-level output voltage	I_{OL} = 4.2 mA		0.4		0.4		0.4	V
I_I	Input current (leakage)	V_{CC} = 5.5 V, V_I = 0 V to 6.5 V, All other pins = 0 V to V_{CC}		± 10		± 10		± 10	µA
I_O	Output current (leakage)	V_{CC} = 5.5 V, V_O = 0 V to V_{CC}, $\overline{CAS}$ high		± 10		± 10		± 10	µA
I_{CC1}	Read- or write-cycle current	V_{CC} = 5.5 V, Minimum cycle		285		250		220	mA
I_{CC2}	Standby current	V_{IH} = 2.4 V (TTL), After 1 memory cycle, $\overline{RAS}$ and $\overline{CAS}$ high		6		6		6	mA
		V_{IH} = V_{CC} – 0.2 V (CMOS), After 1 memory cycle, $\overline{RAS}$ and $\overline{CAS}$ high		3		3		3	mA
I_{CC3}	Average refresh current ($\overline{RAS}$ only or CBR)	V_{CC} = 5.5 V, Minimum cycle, $\overline{RAS}$ cycling, $\overline{CAS}$ high ($\overline{RAS}$ only); $\overline{RAS}$ low after $\overline{CAS}$ low (CBR)		285		250		220	mA
I_{CC4}	Average page current	V_{CC} = 5.5 V, t_{PC} = MIN, $\overline{RAS}$ low, $\overline{CAS}$ cycling		250		220		190	mA

electrical characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted)†

PARAMETER		TEST CONDITIONS	'248NBK36F-60		'248NBK36F-70		'248NBK36F-80		UNIT
			MIN	MAX	MIN	MAX	MIN	MAX	
V_{OH}	High-level output voltage	I_{OH} = – 5 mA	2.4		2.4		2.4		V
V_{OL}	Low-level output voltage	I_{OL} = 4.2 mA		0.4		0.4		0.4	V
I_I	Input current (leakage)	V_{CC} = 5.5 V, V_I = 0 V to 6.5 V, All other pins = 0 V to V_{CC}		± 10		± 10		± 10	µA
I_O	Output current (leakage)	V_{CC} = 5.5 V, V_O = 0 V to V_{CC}, $\overline{CAS}$ high		± 20		± 20		± 20	µA
I_{CC1}	Read- or write-cycle current (see Note 3)	V_{CC} = 5.5 V, Minimum cycle		391		256		226	mA
I_{CC2}	Standby current	V_{IH} = 2.4 V (TTL), After 1 memory cycle, $\overline{RAS}$ and $\overline{CAS}$ high		12		12		12	mA
		V_{IH} = V_{CC} – 0.2 V (CMOS), After 1 memory cycle, $\overline{RAS}$ and $\overline{CAS}$ high		6		6		6	mA
I_{CC3}	Average refresh current ($\overline{RAS}$ only or CBR) (see Note 3)	V_{CC} = 5.5 V, Minimum cycle, $\overline{RAS}$ cycling, $\overline{CAS}$ high ($\overline{RAS}$ only); $\overline{RAS}$ low after $\overline{CAS}$ low (CBR)		570		500		440	mA
I_{CC4}	Average page current (see Note 4)	V_{CC} = 5.5 V, t_{PC} = MIN, $\overline{RAS}$ low, $\overline{CAS}$ cycling		256		226		196	mA

† For test conditions shown as MIN/MAX, use the appropriate value specified under recommended operating conditions.

NOTES: 3. Measured with a maximum of one address change while $\overline{RAS}$ = V_{IL}
4. Measured with a maximum of one address change while $\overline{CAS}$ = V_{IH}

capacitance over recommended ranges of supply voltage and operating free-air temperature, f = 1 MHz (see Note 5)

PARAMETER			'124MBK36F		'248NBK36F		UNIT
			MIN	MAX	MIN	MAX	
$C_{i(A)}$	Input capacitance, address inputs			15		30	pF
$C_{i(R)}$	Input capacitance, RAS inputs	$\overline{RAS2}$, $\overline{RAS3}$		14		14	pF
		$\overline{RAS0}$, $\overline{RAS1}$		7		7	
$C_{i(C)}$	Input capacitance, $\overline{CAS}$ inputs			14		28	pF
$C_{i(W)}$	Input capacitance, write-enable input			21		42	pF
$C_{o(DQ)}$	Output capacitance on DQ pins			7		14	pF

NOTE 5: Bias on pins under test is 0 V.

switching characteristics over recommended ranges of supply voltage and operating free-air temperature

PARAMETER		’124MBK36F-60 ’248NBK36F-60		’124MBK36F-70 ’248NBK36F-70		’124MBK36F-80 ’248NBK36F-80		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
t_{AA}	Access time from column address		30		35		40	ns
t_{CAC}	Access time from $\overline{CAS}$ low		15		18		20	ns
t_{RAC}	Access time from $\overline{RAS}$ low		60		70		80	ns
t_{CPA}	Access time from column precharge		35		40		45	ns
t_{CLZ}	$\overline{CAS}$ to output in low-impedance state	0		0		0		ns
t_{OH}	Output disable time from start of $\overline{CAS}$ high	3		3		3		ns
t_{OFF}	Output disable time after $\overline{CAS}$ high (see Note 6)	0	15	0	18	0	20	ns

NOTE 6: t_{OFF} is specified when the output is no longer driven.

timing requirements over recommended ranges of supply voltage and operating free-air temperature

		’124MBK36F-60 ’248NBK36F-60		’124MBK36F-70 ’248NBK36F-70		’124MBK36F-80 ’248NBK36F-80		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
t_{RC}	Cycle time, random read or write (see Note 7)	110		130		150		ns
t_{PC}	Cycle time, page-mode read or write (see Notes 7 and 8)	40		45		50		ns
t_{RASP}	Pulse duration, page mode, $\overline{RAS}$ low	60	100 000	70	100 000	80	100 000	ns
t_{RAS}	Pulse duration, nonpage mode, $\overline{RAS}$ low	60	10 000	70	10 000	80	10 000	ns
t_{CAS}	Pulse duration, $\overline{CAS}$ low	15	10 000	18	10 000	20	10 000	ns
t_{CP}	Pulse duration, $\overline{CAS}$ high (precharge)	10		10		10		ns
t_{RP}	Pulse duration, $\overline{RAS}$ high (precharge)	40		50		60		ns
t_{WP}	Pulse duration, $\overline{W}$ low	10		10		10		ns
t_{ASC}	Setup time, column address before $\overline{CAS}$ low	0		0		0		ns
t_{ASR}	Setup time, row address before $\overline{RAS}$ low	0		0		0		ns
t_{DS}	Setup time, data before $\overline{CAS}$ low	0		0		0		ns
t_{RCS}	Setup time, $\overline{W}$ high before $\overline{CAS}$ low	0		0		0		ns
t_{CWL}	Setup time, $\overline{W}$ low before $\overline{CAS}$ high	15		18		20		ns
t_{RWL}	Setup time, $\overline{W}$ low before $\overline{RAS}$ high	15		18		20		ns
t_{WCS}	Setup time, $\overline{W}$ low before $\overline{CAS}$ low	0		0		0		ns
t_{WRP}	Setup time, $\overline{W}$ high before $\overline{RAS}$ low (CBR refresh only)	10		10		10		ns
t_{CAH}	Hold time, column address after $\overline{CAS}$ low	10		15		15		ns
t_{RHCP}	Hold time, $\overline{RAS}$ high from $\overline{CAS}$ precharge	35		40		45		ns
t_{DH}	Hold time, data after $\overline{CAS}$ low	10		15		15		ns
t_{RAH}	Hold time, row address after $\overline{RAS}$ low	10		10		10		ns
t_{RCH}	Hold time, $\overline{W}$ high after $\overline{CAS}$ high (see Note 9)	0		0		0		ns
t_{RRH}	Hold time, $\overline{W}$ high after $\overline{RAS}$ high (see Note 9)	0		0		0		ns
t_{WCH}	Hold time, $\overline{W}$ low after $\overline{CAS}$ low	10		15		15		ns
t_{WRH}	Hold time, $\overline{W}$ high after $\overline{RAS}$ low (CBR refresh only)	10		10		10		ns


NOTES: 7. All cycles assume t_T = 5 ns.
8. To assure t_{PC} min, t_{ASC} should be ≥ t_{CP}.
9. Either t_{RRH} or t_{RCH} must be satisfied for a read cycle.

timing requirements over recommended ranges of supply voltage and operating free-air temperature (continued)

		’124MBK36F-60 ’248NBK36F-60		’124MBK36F-70 ’248NBK36F-70		’124MBK36F-80 ’248NBK36F-80		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
t_{CHR}	Delay time, $\overline{RAS}$ low to $\overline{CAS}$ high (CBR refresh only)	10		10		10		ns
t_{CRP}	Delay time, $\overline{CAS}$ high to $\overline{RAS}$ low	5		5		5		ns
t_{CSH}	Delay time, $\overline{RAS}$ low to $\overline{CAS}$ high	60		70		80		ns
t_{CSR}	Delay time, $\overline{CAS}$ low to $\overline{RAS}$ low (CBR refresh only)	5		5		5		ns
t_{RAD}	Delay time, $\overline{RAS}$ low to column address (see Note 10)	15	30	15	35	15	40	ns
t_{RAL}	Delay time, column address to $\overline{RAS}$ high	30		35		40		ns
t_{CAL}	Delay time, column address to $\overline{CAS}$ high	30		35		40		ns
t_{RCD}	Delay time, $\overline{RAS}$ low to $\overline{CAS}$ low (see Note 10)	20	45	20	52	20	60	ns
t_{RPC}	Delay time, $\overline{RAS}$ high to $\overline{CAS}$ low (CBR only)	0		0		0		ns
t_{RSH}	Delay time, $\overline{CAS}$ low to $\overline{RAS}$ high	15		18		20		ns
t_{REF}	Refresh time interval		16		16		16	ms
t_T	Transition time	3	30	3	30	3	30	ns

NOTE 10: The maximum value is specified only to assure access time.

device symbolization (TM124MBK36F illustrated)



YY = Year Code
MM = Month Code
T = Assembly Site Code
-SS = Speed Code

NOTE: Location of symbolization may vary.

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.

Copyright © 1998, Texas Instruments Incorporated