



**Product:** [29529T](#)

VFD 100% Gnd, 3C #1/0 Str TC XLPO Ins + #1/0Symm. Seg. Grd (3 of #4) Str BC, CTS, Blk LSZH Jkt, 600V TC-ER 90C Dry/Wet 1000V Flexible Motor Supply Cable

### Product Description

Belden 100% Ground Flexible VFD, 3 Conductor 1/0AWG (7x19x21) Tinned Copper XLPO Insulation M4 Color Code + 1/0AWG Symmetrically Segmented Ground (3 of 4AWG) Bare Copper Stranded, Overall Dual Copper Tapes Helically Applied Shield, Black LSZH Outer Jacket, 600V TC-ER 90C Dry/Wet 1000V Flexible Motor Supply Cable 1000V CSA AWM I/II A/B SUN RES DIR BUR

### Technical Specifications

#### Physical Characteristics (Overall)

##### Conductor

Stranding	Material
7x19x21	TC - Tinned Copper

##### Temperature Range

UL Temp Rating:	90°C Dry, 90°C Wet
-----------------	--------------------

##### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

#### Part Number

##### Variants

Item #	Color	UPC
29529T 0101000	Black	612825138013
29529T 0102000	Black	612825138020

#### History

Update and Revision:	Revision Number: 0.89 Revision Date: 09-10-2019
----------------------	---

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.