# **SMA Fixed Attenuator**

VAT-15+

 $50\Omega$ 

**1W** 

15dB

DC to 6000 MHz

### **Maximum Ratings**

Operating Temperature -45°C to 100°C Storage Temperature -55°C to 100°C

Permanent damage may occur if any of these limits are exceeded

#### **Features**

- wideband coverage, DC to 6000 MHz
- 1 watt rating
- · rugged unibody construction
- · off-the-shelf availability
- · very low cost

#### **Applications**

- impedance matching
- · signal level adjustment




CASE STYLE: FF704

Connectors SMA VAT-15+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### **Outline Drawing**



## Outline Dimensions (inch )

wt	Е	D	В
grams	.312	1.43	.410
10.0	7.92	36.32	10.41

## **Electrical Specifications**


FREQ. RANGE (MHz)	ATTENUATION * (dB) Flatness **						WR 1)		MAX. INPUT POWER		
		DC-3 GHz	3-5 GHz	5-6 GHz	DC-6 GHz	DC-3	GHz	3-5	GHz	5-6 GHz	(W)
f <sub>L</sub> -f <sub>U</sub>	Nom.	Тур.	Тур.	Тур.	Тур.	Тур.	Max.	Тур.	Max.	Тур.	
DC-6000	15±0.3	0.20	0.30	0.30	0.80	1.05	1.40	1.40	1.80	1.75	1.0


Attenuation varies by 0.3 dB max. over temperature.


# **Typical Performance Data**

Frequency (MHz)	Attenuation (dB)	VSWR (:1)
1	14.97	1.00
50	15.00	1.00
100	15.01	1.00
500.00	15.04	1.01
1000.00	14.98	1.03
2000.00	14.77	1.11
3000.00	14.47	1.21
4000.00	14.22	1.31
5000.00	14.04	1.41
6000.00	13.72	1.54

#### **Electrical Schematic**







A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Terms"): Purchases of this part. Ferrormance and updany authorities and contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

<sup>\*\*</sup> Flatness= variation over band divided by 2.