FLORENTINA-4X1-MRK-W

~50° wide beam. Compatible with ultra high power LEDs.




TECHNICAL SPECIFICATIONS:

Dimensions	169.67x49.67 mm
Height	29.7 mm
Fastening	pin, screw
Colour	black
Box size	476 x 273 x 292 mm
Box weight	3.4 kg
Quantity in Box	72 pcs
ROHS compliant	yes

MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
ROSE-MRK-W	Lens	PC	clear
FLORENTINA-4X1-HLD	Holder	PC	black

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1		FLORENTINA-4x1-HLD	PC	
2		ROSE (4x)	PC	

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class m, otherwise class c.
According to DIN ISO 2768-2
Form and position: class L

THIRD ANGLE PROJECTION:

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

DRAWING TITLE
FLORENTINA-4X1-HLD+LENS

SIZE A3 | PART NUMBER

SCALE 1:1 | WEIGHT 25,33 g | SHEET 1/1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

OSRAM Opto Semiconductors

LED	OSCONIQ P 7070
FWHM	49.0°
Efficiency	79 %
Peak intensity	0.000 cd/lm

Required components:
C15690_FLORENTINA-4X1-SHD-WHT






OSRAM Opto Semiconductors

LED	OSCONIQ P 7070
FWHM	49.0°
Efficiency	74 %
Peak intensity	0.860 cd/lm

Required components:
C15198_FLORENTINA-4X1-SHD-OPEN






OSRAM Opto Semiconductors

LED	OSCONIQ P 7070
FWHM	49.0°
Efficiency	73 %
Peak intensity	0.860 cd/lm

Required components:
C15028_FLORENTINA-4X1-SHD





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.