


FEATURES

- Max. propagation delay of 1000ps
- IEE min. of -58mA
- Extended supply voltage option:
VEE = -4.2V to -5.5V
- Voltage and temperature compensation for improved noise immunity
- Internal 75K Ω input pull-down resistors
- 50% faster than Fairchild 300K at lower power
- Function and pinout compatible with Fairchild F100K
- Available in 24-pin CERPACK and 28-pin PLCC packages


BLOCK DIAGRAM



DESCRIPTION

The SY100S307 is an ultra-fast quint exclusive-OR/NOR gate designed for use in high-performance ECL systems. A function output that is the wire-OR result of the exclusive-OR outputs is also available. The inputs on the device have 75K Ω pull-down resistors.

PIN CONFIGURATIONS



PIN NAMES

Pin	Function
Dna – Dne	Data Inputs (n-1...5)
E	Enable Input
Oa – Oe	Data Outputs
$\overline{Oa} - \overline{Oe}$	Complementary Data Outputs
VEES	VEE Substrate
VCCA	Vcco for ECL Outputs

LOGIC EQUATION

$$F = (D1a \oplus D2a) + (D1b \oplus D2b) + (D1c \oplus D2c) + (D1d \oplus D2d) + (D1e \oplus D2e).$$

DC ELECTRICAL CHARACTERISTICS

$V_{EE} = -4.2V$ to $-5.5V$ unless otherwise specified, $V_{CC} = V_{CCA} = GND$

Symbol	Parameter	Min.	Typ.	Max.	Unit	Condition
I_{IH}	Input HIGH Current D2a — D2e D2a — D2e	— —	— —	200 250	μA	$V_{IN} = V_{IH} (Max.)$
I_{EE}	Power Supply Current	-58	-40	-27	mA	Inputs Open

AC ELECTRICAL CHARACTERISTICS

CERPACK

$V_{EE} = -4.2V$ to $-5.5V$ unless otherwise specified, $V_{CC} = V_{CCA} = GND$


Symbol	Parameter	$T_A = 0^{\circ}C$		$T_A = +25^{\circ}C$		$T_A = +85^{\circ}C$		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Max.		
t_{PLH} t_{PH2}	Propagation Delay D2a — D2e to O, $\bar{O}$	200	1100	200	1150	200	1100	ps	
t_{PLH} t_{PHL}	Propagation Delay D1a — D1e to O, $\bar{O}$	200	1000	200	950	200	1000	ps	
t_{PLH} t_{PHL}	Propagation Delay Data to F	300	1525	300	1525	300	1525	ps	
t_{TLH} t_{THL}	Transition Time 20% to 80%, 80% to 20%	300	900	300	900	300	900	ps	

PLCC

$V_{EE} = -4.2V$ to $-5.5V$ unless otherwise specified, $V_{CC} = V_{CCA} = GND$

Symbol	Parameter	$T_A = 0^{\circ}C$		$T_A = +25^{\circ}C$		$T_A = +85^{\circ}C$		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Max.		
t_{PLH} t_{PH2}	Propagation Delay D2a — D2e to O, $\bar{O}$	300	1000	300	1000	300	1000	ps	
t_{PLH} t_{PHL}	Propagation Delay D1a — D1e to O, $\bar{O}$	300	900	300	900	300	930	ps	
t_{PLH} t_{PHL}	Propagation Delay Data to F	300	1425	300	1425	300	1425	ps	
t_{TLH} t_{THL}	Transition Time 3 20% to 80%, 80% to 20%	00	900	300	900	300	900	ps	

TIMING DIAGRAM




Propagation Delay and Transition Times

NOTE:
 $V_{EE} = -4.2V$ to $-5.5V$ unless otherwise specified, $V_{CC} = V_{CCA} = GND$

PRODUCT ORDERING CODE

Ordering Code	Package Type	Operating Range
SY100S307FC	F24-1	Commercial
SY100S307JC	J28-1	Commercial
SY100S307JCTR	J28-1	Commercial

24 LEAD CERPACK (F24-1)




NOTES:

1. DIMENSIONS ARE IN INCHES[MM].
2. THIS DIMENSION INCLUDES GLASS PROTRUSION AND CAP TO BASE ALIGNMENT TOLERANCES.
3. DIMENSIONS SHOWN ARE MAX/MIN, WHERE NOTED.

Rev. 03

28 LEAD PLCC (J28-1)



Rev. 03

MICREL-SYNERGY 3250 SCOTT BOULEVARD SANTA CLARA CA 95054 USA

TEL + 1 (408) 980-9191 FAX + 1 (408) 914-7878 WEB <http://www.micrel.com>

This information is believed to be accurate and reliable, however no responsibility is assumed by Micrel for its use nor for any infringement of patents or other rights of third parties resulting from its use. No license is granted by implication or otherwise under any patent or patent right of Micrel Inc.

© 2000 Micrel Incorporated