


SECTION A-A

PANEL THICKNESS RANGE	USE WITH
.012 - .051 (0.30 - 1.30)	SR-4050
.051 - .091 (1.30 - 2.30)	SR-4060
.091 - .130 (2.30 - 3.30)	SR-4070
.130 - .169 (3.30 - 4.30)	SR-4080



- NOTES:  
 1. MATERIAL: THERMOPLASTIC ELASTOMER, (RMS-158)  
 2. COLOR: BLACK  
 3. RICHCO SNAP RIVET SR-40XX SOLD SEPERATELY

TITLE:		SHOCK AND VIBRATION FOOT		DWG IN IN[MM]		FINAL		PRINT TYPE	
CREATED USING SOLIDWORKS		FILE #: SVF	DWN: D.J.Z.	APP: DJZ			PART #		CA
TOLERANCES UNLESS NOTED .XX=±.010 .XXX=±.005 FRAC.=±1/64 ANG.=±1°		SHEET: 1 OF 1	SHEET SIZE: A	DT: 05/14/2004	CHKD: SJ	SVF-1			
A	RELEASED FOR PRODUCTION	SM	06/08/04	RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060					
REV.	DESCRIPTION	ENGR.	DATE						