
Marshalling patchboard - PTMC 1,5 /2-2 -NS

3001916

https://www.phoenixcontact.com/us/products/3001916

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Marshalling patchboard, nom. voltage: 500 V, nominal current: 10 A, connection method: Push-in connection, Rated cross section: 1.5 mm^2, cross section: 0.14 mm^2 - 2.5 mm^2, mounting: NS 35/7,5, NS 35/15, color: gray

Your advantages

- For mounting on a DIN rail
- Individual setup thanks to modular principle
- Color configuration possible according to VDE 0812, VDE 0815, DIN 47100 or unlimited.
- Individual color assignment of cable and terminal point to ensure error-free, safe operation
- High contact quality thanks to push-in technology as a replacement for Wire-Wrap®, TERMI-POINT®, etc.
- Tool-free wiring in a confined space thanks to compact size

Commercial Data

Item number	3001916
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	B02
Product Key	BE6212
Catalog Page	Page 68 (C-1-2019)
GTIN	4055626065847
Weight per Piece (including packing)	99.99 g
Weight per Piece (excluding packing)	99.99 g
Customs tariff number	85369010
Country of origin	PL

Technical Data

Product properties

Product type	Marshalling terminal
Number of positions	2
Number of connections	8
Number of rows	1

Insulation characteristics

Overvoltage category	III

Electrical properties

Maximum power dissipation for nominal condition	0.56 W

Connection data

Number of connections per level	8
Nominal cross section	1.5 mm²

Level 1

Stripping length	8 mm ... 10 mm
Conductor cross section solid	0.14 mm² ... 2.5 mm²
Cross section AWG	26 ... 14
Conductor cross section flexible	0.14 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG]	26 ... 14
Flexible conductor cross section flexible (ferrule, w/o plastic sleeve)	0.14 mm² ... 1.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve)	0.14 mm² ... 1.5 mm²
Nominal current	10 A
Maximum load current	22 A
Nominal voltage	500 V
Nominal cross section	1.5 mm²

Level 1 Connection cross sections directly pluggable

Conductor cross section solid	0.34 mm² ... 2.5 mm²
Conductor cross section, solid [AWG]	20 ... 12
Conductor cross section flexible	0.34 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG]	14
Flexible conductor cross section flexible (ferrule, w/o plastic sleeve)	0.34 mm² ... 1.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve)	0.34 mm² ... 1.5 mm²

Dimensions

Width	variable
Height NS 35/15	38.7 mm
Height NS 35/7,5	31.2 mm

Length	63 mm

Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA

Mechanical properties

Mechanical data

Open side panel	No

Environmental and real-life conditions

Ambient conditions


Ambient temperature (operation)	-60 °C ... 85 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

Mounting type	NS 35/7,5
	NS 35/15

Drawings

Circuit diagram



Approvals

CSA
Approval ID: 13631

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Use group B				
	300 V	10 A	24 - 16	-
Use group C				
	300 V	10 A	24 - 16	-
Use group D				
	300 V	10 A	24 - 16	-

EAC
Approval ID: RU C-DE.BL08.B.00682

cULus Recognized
Approval ID: E60425

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Use group B				
	300 V	10 A	24 - 16	-
Use group C				
	300 V	10 A	24 - 16	-

Classifications

ECLASS

ECLASS-9.0	27141120
ECLASS-10.0.1	27141120
ECLASS-11.0	27141120

ETIM

ETIM 8.0	EC000897

UNSPSC

UNSPSC 21.0	39121400

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Accessories

Screwdriver

Screwdriver - SZF 0-0,4X2,5 - 1204504

https://www.phoenixcontact.com/us/products/1204504



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.4 x 2.5 x 75 mm, 2-component grip, with non-slip grip

Test plugs

Test plugs - MPS-MT - 0201744

https://www.phoenixcontact.com/us/products/0201744



Test plugs, with solder connection up to 1 mm^2 conductor cross section, color: gray

Actuation tool

Actuation tool - ST-BW 0 - 1200135

https://www.phoenixcontact.com/us/products/1200135



Actuation tool, for all 1.5 mm^2 spring cages from PT 1,5/S and FT 1,5/S

Insulating sleeve

Insulating sleeve - MPS-IH WH - 0201663

https://www.phoenixcontact.com/us/products/0201663

Insulating sleeve, color: white



Reducing plug

Reducing plug - RPS - 0201647

https://www.phoenixcontact.com/us/products/0201647



Reducing plug, color: gray

Insulating sleeve

Insulating sleeve - MPS-IH RD - 0201676

https://www.phoenixcontact.com/us/products/0201676

Insulating sleeve, color: red




Insulating sleeve

Insulating sleeve - MPS-IH BU - 0201689

https://www.phoenixcontact.com/us/products/0201689

Insulating sleeve, color: blue



Insulating sleeve

Insulating sleeve - MPS-IH YE - 0201692

https://www.phoenixcontact.com/us/products/0201692

Insulating sleeve, color: yellow



Insulating sleeve

Insulating sleeve - MPS-IH GN - 0201702

https://www.phoenixcontact.com/us/products/0201702

Insulating sleeve, color: green



Insulating sleeve

Insulating sleeve - MPS-IH GY - 0201728

https://www.phoenixcontact.com/us/products/0201728

Insulating sleeve, color: gray



Insulating sleeve

Insulating sleeve - MPS-IH BK - 0201731

https://www.phoenixcontact.com/us/products/0201731

Insulating sleeve, color: black



Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com