
High Power Infrared Emitter (850 nm)
Version 1.6

SFH 4056



Features:

- Very small package: (LxWxH) 3.2 mm x 1.6 mm x 1 mm
- High optical total power
- UL version available (ordering code & test conditions on request)

Applications

- Miniature photointerrupters
- Mobile devices
- Proximity sensor
- For control and drive circuits

Notes

Depending on the mode of operation, these devices emit highly concentrated non visible infrared light which can be hazardous to the human eye. Products which incorporate these devices have to follow the safety precautions given in IEC 60825-1 and IEC 62471.

Ordering Information

Type:	Irradiance E_e [mW/cm^2] **I_F= 70 mA, t_p= 20 ms**	Radiant intensity $I_{e, typ}$ [mW/sr] **I_F=70 mA, t_p=20 ms**	Ordering Code
SFH 4056	6 (≥ 2.5)	35	Q65111A2992
SFH 4056-NP	2.5 ... 8		Q65111A9688

Note: *I_e measured with a detector (11.3 mm diameter) in 100 mm distance (Ω = 0.01 sr) to the device surface*

E_e measured in the near field with a detector (7.2 mm diameter) in 20 mm distance (Ω = 0.1 sr) to the device surface

OSRAM Opto Semiconductors

Maximum Ratings (T_A = 25 °C)

Parameter	Symbol	Values	Unit
Operation and storage temperature range	T_{op}; T_{stg}	-40 ... 85	°C
Reverse voltage	V_R	5	V
Forward current	I_F	70	mA
Surge current ($t_p \leq 300$ µs, D = 0)	I_{FSM}	0.7	A
Power consumption	P_{tot}	140	mW
ESD withstand voltage (acc. to ANSI/ ESDA/ JEDEC JS-001 - HBM)	V_{ESD}	2	kV
Thermal resistance junction - ambient [1] *page 13*	R_{thJA}	540	K / W
Thermal resistance junction - soldering point [2] *page 13*	R_{thJS}	360	K / W

Characteristics (T_A = 25 °C)

Parameter		Symbol	Values	Unit
Peak wavelength (I_F = 70 mA, t_p = 20 ms)	(typ)	λ_{peak}	860	nm
Centroid wavelength (I_F = 70 mA, t_p = 20 ms)	(typ)	$\lambda_{centroid}$	850	nm
Spectral bandwidth at 50% of I_{max} (I_F = 70 mA, t_p = 20 ms)	(typ)	$\Delta\lambda$	30	nm
Half angle	(typ)	φ	± 22	°
Dimensions of active chip area	(typ)	L x W	0.2 x 0.2	mm x mm
Rise and fall time of I_e (10% and 90% of $I_{e\,max}$) (I_F = 70 mA, R_L = 50 Ω)	(typ)	t_r, t_f	12	ns
Forward voltage (I_F = 70 mA, t_p = 20 ms)	(typ (max))	V_F	1.6 (≤ 2)	V
Forward voltage (I_F = 500 mA, t_p = 100 µs)	(typ (max))	V_F	2.4	V
Reverse current (V_R = 5 V)		I_R	not designed for reverse operation	µA
Total radiant flux (I_F=70 mA, t_p=20 ms)	(typ)	Φ_e	40	mW
Radiant intensity (I_F=70 mA, t_p=20 ms)		$I_{e,\,min}$ $I_{e,\,typ}$	16 35	mW/sr mW/sr

OSRAM
Opto Semiconductors

Parameter		Symbol	Values	Unit
Temperature coefficient of I_e or Φ_e (I_F = 70 mA, t_p = 20 ms)	(typ)	TC_I	-0.5	% / K
Temperature coefficient of V_F (I_F = 70 mA, t_p = 20 ms)	(typ)	TC_V	-0.7	mV / K
Temperature coefficient of wavelength (I_F = 70 mA, t_p = 20 ms)	(typ)	TC_λ	0.3	nm / K

Grouping (T_A = 25 °C)


Parameter	Min Irradiance I_F= 70 mA, t_p= 20 ms $E_{e, min}$ [mW/cm²]	Max Irradiance I_F= 70 mA, t_p= 20 ms $E_{e, max}$ [mW/cm²]
SFH 4056 -N	2.5	5
SFH 4056 -P	4	8
SFH 4056 -Q	6.3	12.5

Note: *E_e measured in the near field with a detector (7.2 mm diameter) in 20 mm distance (Ω = 0.1 sr) to the device surface*

Only one group in one packing unit (variation lower 2:1).


Relative Spectral Emission 3) *page 13*

(typ) I_{rel} = f(λ), T_A = 25°C



Irradiance 3) *page 13*


E_e/E_e (70mA) = f (I_F), Single pulse, t_p = 25 µs, T_A= 25°C



OSRAM Opto Semiconductors


Max. Permissible Forward Current

$I_{F, max} = f(T_A)$, R_{thJA} = 540 K/W




Forward Current [3] *page 13*

$I_F = f(V_F)$, single pulse, t_p = 100 µs, T_A= 25°C




Permissible Pulse Handling Capability

$I_F = f(t_p)$, T_A = 25 °C, duty cycle D = parameter



Permissible Pulse Handling Capability


$I_F = f(t_p)$, T_A = 85 °C, duty cycle D = parameter



OSRAM Opto Semiconductors


Radiation Characteristics 3) *page 13*

$I_{rel} = f(\phi)$, $T_A = 25°C$



OSRAM Opto Semiconductors

Package Outline



Dimensions in mm.

OSRAM Opto Semiconductors


Pad	Description
1	Cathode
2	Anode

Package
Chipled

Approximate Weight:
5.3 mg

Note:
Colour: black


Recommended Solder Pad



Dimensions in mm.

Reflow Soldering Profile

Product complies to MSL Level 3 acc. to JEDEC J-STD-020D.01



OHA04612


Profile Feature Profil-Charakteristik	Symbol Symbol	Pb-Free (SnAgCu) Assembly			Unit Einheit
		Minimum	Recommendation	Maximum	
Ramp-up rate to preheat*) 25 °C to 150 °C			2	3	K/s
Time t_S T_{Smin} to T_{Smax}	t_S	60	100	120	s
Ramp-up rate to peak*) T_{Smax} to T_P			2	3	K/s
Liquidus temperature	T_L		217		°C
Time above liquidus temperature	t_L		80	100	s
Peak temperature	T_P		245	260	°C
Time within 5 °C of the specified peak temperature T_P - 5 K	t_P	10	20	30	s
Ramp-down rate* T_P to 100 °C			3	6	K/s
Time 25 °C to T_P				480	s

All temperatures refer to the center of the package, measured on the top of the component

* slope calculation DT/Dt: Dt max. 5 s; fulfillment for the whole T-range

OSRAM
Opto Semiconductors


Taping



Dimensions in mm [inch].

Tape and Reel

8 mm tape with 2000 pcs. on ∅ 180 mm reel



Leader: min. 400 mm *
Trailer: min. 160 mm *
*) Dimensions acc. to IEC 60286-3; EIA 481-D

OHAY0324

OSRAM Opto Semiconductors


Tape dimensions [mm]

W	P_0	P_1	P_2	D_0	E	F
8 + 0.3 / -0.1	4 ± 0.1	2 ± 0.05 or 4 ± 0.1	2 ± 0.05	1.5 ± 0.1	1.75 ± 0.1	3.5 ± 0.05


Reel dimensions [mm]

A	W	N_{min}	W_1	W_{2max}
180	8	60	8.4 + 2	14.4

Barcode-Product-Label (BPL)




Dry Packing Process and Materials



Note:
Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card.
Regarding dry pack you will find further information in the internet. Here you will also find the normative references like JEDEC.

Transportation Packing and Materials



Dimensions of transportation box in mm

Width	Length	Height
200 ± 5	195 ± 5	30 ± 5

Disclaimer

Language english will prevail in case of any discrepancies or deviations between the two language wordings.

Attention please!
The information describes the type of component and shall not be considered as assured characteristics.
Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.
For information on the types in question please contact our Sales Organization.
If printed or downloaded, please find the latest version in the Internet.
Packing
Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.
Components used in life-support devices or systems must be expressly authorized for such purpose!
Critical components* may only be used in life-support devices** or systems with the express written approval of OSRAM OS.

*) A critical component is a component used in a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or the effectiveness of that device or system.
**) Life support devices or systems are intended (a) to be implanted in the human body, or (b) to support and/or maintain and sustain human life. If they fail, it is reasonable to assume that the health and the life of the user may be endangered.

Glossary

[1] **Thermal resistance:** junction -ambient, mounted on PC-board (FR4), padsize 5 mm^2 each

[2] **Thermal resistance:** junction - soldering point, of the device only, mounted on an ideal heatsink (e.g. metal block)

[3] **Typical Values:** Due to the special conditions of the manufacturing processes of LED, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.

Published by OSRAM Opto Semiconductors GmbH
Leibnizstraße 4, D-93055 Regensburg
www.osram-os.com © All Rights Reserved.

EU RoHS and China RoHS compliant product

此产品符合欧盟 RoHS 指令的要求；

按照中国的相关法规和标准，不含有毒有害物质或元素。

OSRAM
Opto Semiconductors