

## Quad 300MHz Current Feedback Amplifier with Enable



The EL5493 and EL5493A are quad current feedback amplifiers with a bandwidth of 300MHz. This makes

these amplifiers ideal for today's high speed video and monitor applications.


With a supply current of just 4mA per amplifier and the ability to run from a single supply voltage from 5V to 10V, these amplifiers are also ideal for hand held, portable or battery powered equipment.

The EL5493A also incorporates an enable and disable function to reduce the supply current to 100µA typical per amplifier. Allowing the  $\overline{CE}$  pin to float or applying a low logic level will enable the amplifier.


The EL5493 is offered in the industry-standard 14-pin SO (0.150") package and the EL5493A in the ultra-small 24-pin LPP package. Both operate over the industrial temperature range of -40°C to +85°C.

## Pinouts

**EL5493A**  
**(24-PIN LPP)**  
TOP VIEW



**EL5493**  
**[14-PIN SO (0.150")]**  
TOP VIEW



## Features

- 300MHz -3dB bandwidth
- 4mA supply current (per amplifier)
- Single and dual supply operation, from 5V to 10V
- Fast enable/disable (EL5493A only)
- Single (EL5193), dual (EL5293), and triple (EL5393) available
- High speed, 1GHz product available (EL5191)
- High speed, 6mA, 600MHz product available (EL5192, EL5292, EL5392 & EL5492)

## Applications

- Battery-powered equipment
- Hand-held, portable devices
- Video amplifiers
- Cable drivers
- RGB amplifiers
- Test equipment
- Instrumentation
- Current to voltage converters

## Ordering Information

| PART NUMBER   | PACKAGE            | TAPE & REEL | PKG. NO. |
|---------------|--------------------|-------------|----------|
| EL5493CS      | 14-Pin SO (0.150") | -           | MDP0027  |
| EL5493CS-T7   | 14-Pin SO (0.150") | 7"          | MDP0027  |
| EL5493CS-T13  | 14-Pin SO (0.150") | 13"         | MDP0027  |
| EL5493ACL     | 24-Pin LPP         | -           | MDP0046  |
| EL5493ACL-T7  | 24-Pin LPP         | 7"          | MDP0046  |
| EL5493ACL-T13 | 24-Pin LPP         | 13"         | MDP0046  |

## Absolute Maximum Ratings (T<sub>A</sub> = 25°C)

Supply Voltage between V<sub>S+</sub> and V<sub>S-</sub> ..... 11V  
 Maximum Continuous Output Current ..... 50mA  
 Operating Junction Temperature ..... 125°C  
 Power Dissipation ..... See Curves

Pin Voltages ..... V<sub>S-</sub> -0.5V to V<sub>S+</sub> +0.5V  
 Storage Temperature ..... -65°C to +150°C  
 Ambient Operating Temperature ..... -40°C to +85°C

**CAUTION:** Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

**IMPORTANT NOTE:** All parameters having Min/Max specifications are guaranteed. Typical values are for information purposes only. Unless otherwise noted, all tests are at the specified temperature and are pulsed tests, therefore: T<sub>J</sub> = T<sub>C</sub> = T<sub>A</sub>

**Electrical Specifications** V<sub>S+</sub> = +5V, V<sub>S-</sub> = -5V, R<sub>F</sub> = 750Ω for A<sub>V</sub> = 1, R<sub>F</sub> = 375Ω for A<sub>V</sub> = 2, R<sub>L</sub> = 150Ω, T<sub>A</sub> = 25°C unless otherwise specified.

| PARAMETER                      | DESCRIPTION                                  | CONDITIONS                                             | MIN  | TYP  | MAX | UNIT   |
|--------------------------------|----------------------------------------------|--------------------------------------------------------|------|------|-----|--------|
| <b>AC PERFORMANCE</b>          |                                              |                                                        |      |      |     |        |
| BW                             | -3dB Bandwidth                               | A <sub>V</sub> = +1                                    |      | 300  |     | MHz    |
|                                |                                              | A <sub>V</sub> = +2                                    |      | 200  |     | MHz    |
| BW1                            | 0.1dB Bandwidth                              |                                                        |      | 20   |     | MHz    |
| SR                             | Slew Rate                                    | V <sub>O</sub> = -2.5V to +2.5V, A <sub>V</sub> = +2   | 1900 | 2200 |     | V/μs   |
| t <sub>S</sub>                 | 0.1% Settling Time                           | V <sub>OUT</sub> = -2.5V to +2.5V, A <sub>V</sub> = -1 |      | 12   |     | ns     |
| C <sub>S</sub>                 | Channel Separation                           | f = 5MHz                                               |      | 60   |     | dB     |
| e <sub>N</sub>                 | Input Voltage Noise                          |                                                        |      | 4.4  |     | nV/√Hz |
| i <sub>N-</sub>                | IN- Input Current Noise                      |                                                        |      | 17   |     | pA/√Hz |
| i <sub>N+</sub>                | IN+ Input Current Noise                      |                                                        |      | 50   |     | pA/√Hz |
| dG                             | Differential Gain Error (Note 1)             | A <sub>V</sub> = +2                                    |      | 0.03 |     | %      |
| dP                             | Differential Phase Error (Note 1)            | A <sub>V</sub> = +2                                    |      | 0.04 |     | °      |
| <b>DC PERFORMANCE</b>          |                                              |                                                        |      |      |     |        |
| V <sub>OS</sub>                | Offset Voltage                               |                                                        | -10  | 1    | 10  | mV     |
| T <sub>C</sub> V <sub>OS</sub> | Input Offset Voltage Temperature Coefficient | Measured from T <sub>MIN</sub> to T <sub>MAX</sub>     |      | 5    |     | μV/°C  |
| R <sub>OL</sub>                | Transimpedance                               |                                                        | 300  | 600  |     | kΩ     |
| <b>INPUT CHARACTERISTICS</b>   |                                              |                                                        |      |      |     |        |
| CMIR                           | Common Mode Input Range                      |                                                        | ±3   | ±3.3 |     | V      |
| CMRR                           | Common Mode Rejection Ratio                  |                                                        | 42   | 50   |     | dB     |
| +I <sub>IN</sub>               | + Input Current                              |                                                        | -60  | 1    | 80  | μA     |
| -I <sub>IN</sub>               | - Input Current                              |                                                        | -35  | 1    | 35  | μA     |
| R <sub>IN</sub>                | Input Resistance                             |                                                        |      | 45   |     | kΩ     |
| C <sub>IN</sub>                | Input Capacitance                            |                                                        |      | 0.5  |     | pF     |
| <b>OUTPUT CHARACTERISTICS</b>  |                                              |                                                        |      |      |     |        |
| V <sub>O</sub>                 | Output Voltage Swing                         | R <sub>L</sub> = 150Ω to GND                           | ±3.4 | ±3.7 |     | V      |
|                                |                                              | R <sub>L</sub> = 1kΩ to GND                            | ±3.8 | ±4.0 |     | V      |
| I <sub>OUT</sub>               | Output Current                               | R <sub>L</sub> = 10Ω to GND                            | 95   | 120  |     | mA     |
| <b>SUPPLY</b>                  |                                              |                                                        |      |      |     |        |
| I <sub>SON</sub>               | Supply Current - Enabled (per amplifier)     | No load, V <sub>IN</sub> = 0V                          | 3    | 4    | 5   | mA     |
| I <sub>SOFF</sub>              | Supply Current - Disabled                    | No load, V <sub>IN</sub> = 0V                          |      | 100  | 150 | μA     |
| PSRR                           | Power Supply Rejection Ratio                 | DC, V <sub>S</sub> = ±4.75V to ±5.25V                  | 55   | 75   |     | dB     |
| -IPSR                          | - Input Current Power Supply Rejection       | DC, V <sub>S</sub> = ±4.75V to ±5.25V                  | -2   |      | 2   | μA/V   |

## EL5493, EL5493A







**Electrical Specifications**  $V_{S+} = +5V$ ,  $V_{S-} = -5V$ ,  $R_F = 750\Omega$  for  $A_V = 1$ ,  $R_F = 375\Omega$  for  $A_V = 2$ ,  $R_L = 150\Omega$ ,  $T_A = 25^\circ C$  unless otherwise specified. **(Continued)**

| PARAMETER                    | DESCRIPTION                          | CONDITIONS               | MIN          | TYP | MAX          | UNIT    |
|------------------------------|--------------------------------------|--------------------------|--------------|-----|--------------|---------|
| <b>ENABLE (EL5493A ONLY)</b> |                                      |                          |              |     |              |         |
| $t_{EN}$                     | Enable Time                          |                          |              | 40  |              | ns      |
| $t_{DIS}$                    | Disable Time (Note 2)                |                          |              | 600 |              | ns      |
| $I_{IHCE}$                   | CE Pin Input High Current            | $\overline{CE} = V_{S+}$ |              | 0.8 | 6            | $\mu A$ |
| $I_{ILCE}$                   | CE Pin Input Low Current             | $\overline{CE} = V_{S-}$ |              | 0   | -0.1         | $\mu A$ |
| $V_{IHCE}$                   | CE Input High Voltage for Power-down |                          | $V_{S+} - 1$ |     |              | V       |
| $V_{ILCE}$                   | CE Input Low Voltage for Power-down  |                          |              |     | $V_{S+} - 3$ | V       |







**NOTES:**

1. Standard NTSC test, AC signal amplitude =  $286mV_{P-P}$ ,  $f = 3.58MHz$
2. Measured from the application of  $\overline{CE}$  logic signal until the output voltage is at the 50% point between initial and final values







## Typical Performance Curves









# Typical Performance Curves (Continued)









Typical Performance Curves (Continued)



## Typical Performance Curves (Continued)









## Typical Performance Curves (Continued)











# Typical Performance Curves (Continued)




Typical Performance Curves (Continued)




## Typical Performance Curves (Continued)


Channel-to-Channel Isolation vs Frequency




Enable Response




Disable Response



Package Power Dissipation vs Ambient Temperature  
JEDEC JESD51-3 Low Effective Thermal Conductivity (Single Layer) Test Board



Package Power Dissipation vs Ambient Temperature  
JEDEC JESD51-7 High Effective Thermal Conductivity (4 layer) Test Board - LPP exposed diepad soldered to PCB per JESD51-5



## Pin Descriptions

| 14-PIN SO<br>(0.150") | 24-PIN LPP              | PIN NAME                | FUNCTION                       | EQUIVALENT CIRCUIT |
|-----------------------|-------------------------|-------------------------|--------------------------------|--------------------|
| 1                     | 23                      | OUTA                    | Output, channel A              | <p>Circuit 1</p>   |
| 2                     | 24                      | INA-                    | Inverting input, channel A     | <p>Circuit 2</p>   |
| 3                     | 2                       | INA+                    | Non-inverting input, channel A | (see circuit 2)    |
|                       | 3                       | $\overline{\text{CEA}}$ | Chip enable, channel A         | <p>Circuit 3</p>   |
| 4                     | 4                       | VS+                     | Positive supply                |                    |
|                       | 5                       | $\overline{\text{CEB}}$ | Chip enable, channel B         | (see circuit 3)    |
| 5                     | 6                       | INB+                    | Non-inverting input, channel B | (see circuit 2)    |
| 6                     | 8                       | INB-                    | Inverting input, channel B     | (see circuit 2)    |
| 7                     | 9                       | OUTB                    | Output, channel B              | (see circuit 1)    |
| 8                     | 11                      | OUTC                    | Output, channel C              | (see circuit 1)    |
| 9                     | 12                      | INC-                    | Inverting input, channel C     | (see circuit 2)    |
| 10                    | 14                      | INC+                    | Non-inverting input, channel C | (see circuit 2)    |
|                       | 15                      | $\overline{\text{CEC}}$ | Chip enable, channel C         | (see circuit 3)    |
| 11                    | 16                      | VS-                     | Negative supply                |                    |
|                       | 17                      | CED                     | Chip enable, channel D         | (see circuit 3)    |
| 12                    | 18                      | IND+                    | Non-inverting input, channel D | (see circuit 2)    |
| 13                    | 20                      | IND-                    | Inverting input, channel D     | (see circuit 1)    |
| 14                    | 21                      | OUTD                    | Output, channel D              | (see circuit 1)    |
|                       | 1, 7, 10, 13,<br>19, 22 | NC                      | No connection                  |                    |

## Applications Information

### Product Description

The EL5493 is a current-feedback operational amplifier that offers a wide -3dB bandwidth of 300MHz and a low supply current of 4mA per amplifier. The EL5493 works with supply voltages ranging from a single 5V to 10V and they are also capable of swinging to within 1V of either supply on the output. Because of its current-feedback topology, the EL5493 does not have the normal gain-bandwidth product associated with voltage-feedback operational amplifiers. Instead, its -3dB bandwidth to remain relatively constant as closed-loop gain is increased. This combination of high bandwidth and low power, together with aggressive pricing make the EL5493 the ideal choice for many low-power/high-bandwidth applications such as portable, handheld, or battery-powered equipment.

For varying bandwidth needs, consider the EL5191 with 1GHz on a 9mA supply current or the EL5192 with 600MHz on a 6mA supply current. Versions also include single, dual, triple, and quad amp packages.

### Power Supply Bypassing and Printed Circuit Board Layout

As with any high frequency device, good printed circuit board layout is necessary for optimum performance. Low impedance ground plane construction is essential. Surface mount components are recommended, but if leaded components are used, lead lengths should be as short as possible. The power supply pins must be well bypassed to reduce the risk of oscillation. The combination of a 4.7 $\mu$ F tantalum capacitor in parallel with a 0.01 $\mu$ F capacitor has been shown to work well when placed at each supply pin.

For good AC performance, parasitic capacitance should be kept to a minimum, especially at the inverting input. (See the Capacitance at the Inverting Input section) Even when ground plane construction is used, it should be removed from the area near the inverting input to minimize any stray capacitance at that node. Carbon or Metal-Film resistors are acceptable with the Metal-Film resistors giving slightly less peaking and bandwidth because of additional series inductance. Use of sockets, particularly for the SO (0.150") package, should be avoided if possible. Sockets add parasitic inductance and capacitance which will result in additional peaking and overshoot.

### Disable/Power-Down

The EL5493A amplifier can be disabled placing its output in a high impedance state. When disabled, the amplifier supply current is reduced to < 600 $\mu$ A. The EL5493A is disabled when its  $\overline{\text{CE}}$  pin is pulled up to within 1V of the positive supply. Similarly, the amplifier is enabled by floating or pulling its  $\overline{\text{CE}}$  pin to at least 3V below the positive supply. For  $\pm 5$ V supply, this means that an EL5493A amplifier will be enabled when  $\overline{\text{CE}}$  is 2V or less, and disabled when  $\overline{\text{CE}}$  is

above 4V. Although the logic levels are not standard TTL, this choice of logic voltages allows the EL5493A to be enabled by tying  $\overline{\text{CE}}$  to ground, even in 5V single supply applications. The  $\overline{\text{CE}}$  pin can be driven from CMOS outputs.

### Capacitance at the Inverting Input

Any manufacturer's high-speed voltage- or current-feedback amplifier can be affected by stray capacitance at the inverting input. For inverting gains, this parasitic capacitance has little effect because the inverting input is a virtual ground, but for non-inverting gains, this capacitance (in conjunction with the feedback and gain resistors) creates a pole in the feedback path of the amplifier. This pole, if low enough in frequency, has the same destabilizing effect as a zero in the forward open-loop response. The use of large-value feedback and gain resistors exacerbates the problem by further lowering the pole frequency (increasing the possibility of oscillation.)

The EL5493 has been optimized with a 475 $\Omega$  feedback resistor. With the high bandwidth of these amplifiers, these resistor values might cause stability problems when combined with parasitic capacitance, thus ground plane is not recommended around the inverting input pin of the amplifier.

### Feedback Resistor Values

The EL5493 has been designed and specified at a gain of +2 with  $R_F$  approximately 500 $\Omega$ . This value of feedback resistor gives 200MHz of -3dB bandwidth at  $A_V=2$  with 2dB of peaking. With  $A_V=-2$ , an  $R_F$  of approximately 500 $\Omega$  gives 175MHz of bandwidth with 0.2dB of peaking. Since the EL5493 is a current-feedback amplifier, it is also possible to change the value of  $R_F$  to get more bandwidth. As seen in the curve of Frequency Response for Various  $R_F$  and  $R_G$ , bandwidth and peaking can be easily modified by varying the value of the feedback resistor.

Because the EL5493 is a current-feedback amplifier, its gain-bandwidth product is not a constant for different closed-loop gains. This feature actually allows the EL5493 to maintain about the same -3dB bandwidth. As gain is increased, bandwidth decreases slightly while stability increases. Since the loop stability is improving with higher closed-loop gains, it becomes possible to reduce the value of  $R_F$  below the specified 475 $\Omega$  and still retain stability, resulting in only a slight loss of bandwidth with increased closed-loop gain.

### Supply Voltage Range and Single-Supply Operation

The EL5493 has been designed to operate with supply voltages having a span of greater than 5V and less than 10V. In practical terms, this means that the EL5493 will operate on dual supplies ranging from  $\pm 2.5$ V to  $\pm 5$ V. With single-supply, the EL5493 will operate from 5V to 10V.

As supply voltages continue to decrease, it becomes necessary to provide input and output voltage ranges that

can get as close as possible to the supply voltages. The EL5493 has an input range which extends to within 2V of either supply. So, for example, on +5V supplies, the EL5493 has an input range which spans  $\pm 3V$ . The output range of the EL5493 is also quite large, extending to within 1V of the supply rail. On a  $\pm 5V$  supply, the output is therefore capable of swinging from -4V to +4V. Single-supply output range is larger because of the increased negative swing due to the external pull-down resistor to ground.

### Video Performance

For good video performance, an amplifier is required to maintain the same output impedance and the same frequency response as DC levels are changed at the output. This is especially difficult when driving a standard video load of  $150\Omega$ , because of the change in output current with DC level. Previously, good differential gain could only be achieved by running high idle currents through the output transistors (to reduce variations in output impedance.) These currents were typically comparable to the entire 4mA supply current of each EL5493 amplifier. Special circuitry has been incorporated in the EL5493 to reduce the variation of output impedance with current output. This results in dG and dP specifications of 0.03% and  $0.04^\circ C$ , while driving  $150\Omega$  at a gain of 2.

Video performance has also been measured with a  $500\Omega$  load at a gain of +1. Under these conditions, the EL5493 has dG and dP specifications of 0.03% and  $0.04^\circ C$ .

### Output Drive Capability

In spite of its low 4mA of supply current, the EL5493 is capable of providing a minimum of  $\pm 95mA$  of output current. With a minimum of  $\pm 95mA$  of output drive, the EL5493 is capable of driving  $50\Omega$  loads to both rails, making it an excellent choice for driving isolation transformers in telecommunications applications.

### Driving Cables and Capacitive Loads

When used as a cable driver, double termination is always recommended for reflection-free performance. For those applications, the back-termination series resistor will decouple the EL5493 from the cable and allow extensive capacitive drive. However, other applications may have high capacitive loads without a back-termination resistor. In these applications, a small series resistor (usually between  $5\Omega$  and  $50\Omega$ ) can be placed in series with the output to eliminate most peaking. The gain resistor ( $R_G$ ) can then be chosen to make up for any gain loss which may be created by this additional resistor at the output. In many cases it is also

possible to simply increase the value of the feedback resistor ( $R_F$ ) to reduce the peaking.

### Current Limiting

The EL5493 has no internal current-limiting circuitry. If the output is shorted, it is possible to exceed the Absolute Maximum Rating for output current or power dissipation, potentially resulting in the destruction of the device.

### Power Dissipation

With the high output drive capability of the EL5493, it is possible to exceed the  $125^\circ C$  Absolute Maximum junction temperature under certain very high load current conditions. Generally speaking when  $R_L$  falls below about  $25\Omega$ , it is important to calculate the maximum junction temperature ( $T_{JMAX}$ ) for the application to determine if power supply voltages, load conditions, or package type need to be modified for the EL5493 to remain in the safe operating area. These parameters are calculated as follows:

$$T_{JMAX} = T_{MAX} + (\theta_{JA} \times n \times PD_{MAX})$$

where:

$T_{MAX}$  = Maximum ambient temperature

$\theta_{JA}$  = Thermal resistance of the package

$n$  = Number of amplifiers in the package

$PD_{MAX}$  = Maximum power dissipation of each amplifier in the package

$PD_{MAX}$  for each amplifier can be calculated as follows:

$$PD_{MAX} = (2 \times V_S \times I_{SMAX}) + \left[ (V_S - V_{OUTMAX}) \times \frac{V_{OUTMAX}}{R_L} \right]$$

where:

$V_S$  = Supply voltage

$I_{SMAX}$  = Maximum supply current of 1A

$V_{OUTMAX}$  = Maximum output voltage (required)

$R_L$  = Load resistance

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9000 quality systems. Intersil Corporation's quality certifications can be viewed at [www.intersil.com/design/quality](http://www.intersil.com/design/quality)

*Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.*

For information regarding Intersil Corporation and its products, see [www.intersil.com](http://www.intersil.com)