

ワイヤ-レンジ
WIRE RANGE
ID MARK

—TOOLING ID MARK
ON OUTER SURFACE

SECTION "A-A"

SECTION B-B

Technical drawing of a pressure ID-mark on a metal part. The drawing shows a cross-section of a component with a complex profile. Key dimensions are indicated: a total length of 17.8 with a tolerance of ± 0.5 , a segment of 9.3, and a segment of 2.5. Two vertical lines are labeled "A" and "B". A circular feature is labeled めっきコード (PLATING ID-NO). A rectangular area is labeled 接圧表示 (PRESSURE ID-MARK).

注記

- ① 低接圧型コンタクト : 一般向け及び多極用
② 高接圧型コンタクト : 高電流用及び強振動用
③ 金めっきは接触部のみとする

NOTES

- △ CONTACT TYPE, LOW PRESSURE TYPE (FOR GENERAL)
△ CONTACT TYPE, HIGH PRESSURE TYPE
(FOR HIGH CURRENT OR ANTI-VIBRATION)
△ GOLD-PL. CONTACT AREA ONLY

△2	H	5	光沢錫めっき (BRIGHT TIN-PL.)	1-	↑ -5
		3	0.75μm最小金めっき (0.75μmMIN. Au-PL.)	1-	-3
		2	0.38μm最小金めっき (0.38μmMIN. Au-PL.)	1-	-2
△1	OBSOLETE	5	光沢錫めっき (BRIGHT TIN-PL.)		-5
		3	0.75μm最小金めっき (0.75μmMIN. Au-PL.)		-3
		2	0.38μm最小金めっき (0.38μmMIN. Au-PL.)		
備考 (REMARK)	標圧表示 (ID-MARK)	めっきコード (PL. ID NO)	仕上 (FINISH)	A	175194-2
標圧タイプ (CONT. TYPE)					型番 (P/N)



TE Connectivity

B	REVISED PER ECR-15-011723	Y.O	ET	08AUG 2015
A3	REVISED PER ECO-11-005294	RK	HMR	06APR 11
LTR	REVISION RECORD	DR	CHK	DATE

適合電線断面積 (WIRE RANGE) AWG 28-24 (0.08-0.2mm ²)		被覆外径 (INSULATION DIA.) 0.8-1.4 mmφ		名称 (NAME) "S" SIZE (DYNAMIC SERIES REC. CONTACT) ダイナミックシリーズリセブタクルコンタクト				
材料 (MATERIAL) (COPPER ALLOY) 銅合金		仕上 (FINISH) (SEE TABLE) 表参照		一般公差 (GENERAL TOLERANCE) 10mm以下 ±0.2 10mm超え 30mm以下 ±0.25 30mm超え 100mm以下 ±0.3 角 度 ±3°		SIZE B	LOC J	番号 (No.) 175194
DR. 5/27/90 T-YONEBAYASHI	DE. T-YONEBAYASHI	CHK. 14 FEB '91 H. OBATA	APP. 14 FEB '91 S. MANABE	尺 度 (SCALE) S-1		REV. B	SHEET 1 OF 1	

(CUSTOMER DRAWING) 参 考 ☒ 面