



Male (With Metal cover)

Product Specification

Material

Insulator :Glass-Filled Thermoplastic PBT,UL94V-0 rated, Blue
 Contact :Brass , Gold flash selective gold
 Shell :Steel, 100u" Tin Over 50u" min Nickel.

Electrical

Contact Resistance :20 milliohms Max at 1 AMP DC.
 Insulation Resistance :1000 magohms at 500 VDC
 Dielectric Withstanding Voltage :1000 VAC/rms 60Hz for 1 minute
 Current Rating :5 AMP
 Volatge Rating :250 VAC/rms 60Hz

Dimensions

Positions	A	B	C	D
14	17.32	25.50	38.08	21.40
24	27.94	36.20	49.28	20.40
36	41.00	49.20	61.96	22.63
50	56.32	64.30	77.00	24.74

RoHS compliant

Scale	1:1						Date	Name	Customer-No.
TOLERANCE						Drawn	30.06.2009	Dean	ASSMANN WSW-No. A-57/xx M
X.	±0.38					Approved	30.06.2009	Hellwig	
X.X	±0.25								
X.XX	±0.13								
X°	±3°								
.X°	±1.0°								Drawing-No.
		①	Drawn	30.06.2009	Dean	ASSMANN WSW components		ASS 3547 CO	rev01
		Id.	Modification	Date	Name			Replace	Sheet

RoHS compliant