



DASH NO.	A REF	B REF	C ±.010	D ±.010
MS9167-01	0.562	0.500	0.328	0.328
MS9167-02	0.562	0.625	0.328	0.453
MS9167-03	0.562	0.750	0.328	0.578
MS9167-04	0.562	0.875	0.328	0.703
MS9167-05	0.562	1.000	0.328	0.828
MS9167-06	0.562	1.250	0.328	1.078
MS9167-07	0.562	1.500	0.328	1.328
MS9167-10	0.688	0.500	0.453	0.328
MS9167-11	0.688	0.625	0.453	0.453
MS9167-12	0.688	0.750	0.453	0.578
MS9167-13	0.688	0.875	0.453	0.703
MS9167-14	0.688	1.000	0.453	0.828
MS9167-15	0.688	1.250	0.453	1.078
MS9167-16	0.688	1.500	0.453	1.328
MS9167-20	0.812	0.500	0.578	0.328
MS9167-21	0.812	0.625	0.578	0.453
MS9167-22	0.812	0.750	0.578	0.578
MS9167-23	0.812	0.875	0.578	0.703
MS9167-24	0.812	1.000	0.578	0.828
MS9167-25	0.812	1.250	0.578	1.078
MS9167-26	0.812	1.500	0.578	1.328
MS9167-30	0.938	0.500	0.703	0.328
MS9167-31	0.938	0.625	0.703	0.453
MS9167-32	0.938	0.750	0.703	0.578
MS9167-33	0.938	0.875	0.703	0.703
MS9167-34	0.938	1.000	0.703	0.828
MS9167-35	0.938	1.250	0.703	1.078
MS9167-36	0.938	1.500	0.703	1.328

DASH NO.	A REF	B REF	C ±.010	D ±.010
MS9167-40	1.062	0.500	0.828	0.328
MS9167-41	1.062	0.625	0.828	0.453
MS9167-42	1.062	0.750	0.828	0.578
MS9167-43	1.062	0.875	0.828	0.703
MS9167-44	1.062	1.000	0.828	0.828
MS9167-45	1.062	1.250	0.828	1.078
MS9167-46	1.062	1.500	0.828	1.328
MS9167-50	1.312	0.500	1.078	0.328
MS9167-51	1.312	0.625	1.078	0.453
MS9167-52	1.312	0.750	1.078	0.578
MS9167-53	1.312	0.875	1.078	0.703
MS9167-54	1.312	1.000	1.078	0.828
MS9167-55	1.312	1.250	1.078	1.078
MS9167-56	1.312	1.500	1.078	1.328
MS9167-60	1.562	0.500	1.328	0.328
MS9167-61	1.562	0.625	1.328	0.453
MS9167-62	1.562	0.750	1.328	0.578
MS9167-63	1.562	0.875	1.328	0.703
MS9167-64	1.562	1.000	1.328	0.828
MS9167-65	1.562	1.250	1.328	1.078
MS9167-66	1.562	1.500	1.328	1.328
MS9167-70	1.812	0.500	1.578	0.328
MS9167-71	1.812	0.625	1.578	0.453
MS9167-72	1.812	0.750	1.578	0.578
MS9167-73	1.812	0.875	1.578	0.703
MS9167-74	1.812	1.000	1.578	0.828
MS9167-75	1.812	1.250	1.578	1.078
MS9167-76	1.812	1.500	1.578	1.328

REQUIREMENTS:

MATERIAL: STEEL AMS 6350. HARDEN (OIL QUANCH) AND TEMPER TO ROCKWELL C 32-38.

FINISH: CADMIUM PLATE PER AMS 2400. DIMENSIONS SPECIFIED ARE AFTER PLATING

REMOVE BURRS AND BREAK SHARP EDGES.

ALL DIMENSIONS ARE IN INCHES. UNLESS OTHERWISE SPECIFIED: TOLERANCES; LINEAR ±.015

DO NOT USE UNASSIGNED PART NUMBERS.

THIS CATALOG PAGE IS FOR REFERENCE ONLY. REQUEST A CERTIFIED UMPCO DRAWING FOR ACTUAL SPECIFICATIONS. ANY CONFLICT BETWEEN THIS DOCUMENT AND THE CERTIFIED DRAWING, THE CERTIFIED DRAWING WILL TAKE PRESEDENCE. IF THE DOCUMENT IS CONTROLLED BY ANY OTHER SOURCE THAN UMPCO, THE CERTIFIED DRAWING MUST BE PURCHASED THROUGH THAT ORGANIZATION.

UMPCO, INC
CAGE CODE No. 18076

REV
N/C
01/30/09

MS9167

BRACKET, 90° ANGLE, AMS 6350, .190 X .312 BOLT

PART NUMBER