

0669	0670	0673	0666
<p>0669-0-15-XX-30-XX-10-0 Solder mount in 1,52 min. mounting hole Also available on 16mm wide carrier tape: 1,700 parts per 330mm reel. Order as: 0669-0-57-XX-30-XX-10-0</p>	<p>0670-0-15-XX-30-XX-10-0 Solder mount in 1,52 min. mounting hole</p>	<p>0673-0-15-XX-30-XX-10-0 Surface Mount</p>	<p>0666-0-15-XX-32-XX-10-0 Solder mount in 1,63 min. mounting hole Also available on 24mm wide carrier tape: 1,500 parts per 330mm reel. Order as: 0666-0-57-XX-32-XX-10-0</p>

0341	0252	0678	0676
<p>0341-0-15-XX-30-XX-10-0 Solder mount in 1,85 mounting hole Also available on 12mm wide carrier tape: 1,400 parts per 330mm reel. Order as: 0341-0-57-XX-30-XX-10-0</p>	<p>0252-0-15-XX-32-XX-10-0 Hex press-fit in 1,45 plated thru hole</p>	<p>0678-0-15-XX-32-XX-10-0 Press-fit in 1,45 mounting hole</p>	<p>0676-0-15-XX-30-XX-10-0 Press-fit in 1,45 mounting hole</p>

0697	0668	0253/1033									
<p>0697-0-15-XX-30-XX-10-0 Press-fit in 1,45 mounting hole</p>	<p>0668-0-15-XX-30-XX-10-0 Press-fit in 1,45 mounting hole</p>	<p>XXX3-0-15-XX-30-XX-10-0 Press-fit in 1,45 mounting hole</p>									
		<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Length L</th> <th>Depth N</th> </tr> </thead> <tbody> <tr> <td>0253-0</td> <td>4,39</td> <td>3,76</td> </tr> <tr> <td>1033-0</td> <td>5,16</td> <td>4,11</td> </tr> </tbody> </table>	Basic Part Number	Length L	Depth N	0253-0	4,39	3,76	1033-0	5,16	4,11
Basic Part Number	Length L	Depth N									
0253-0	4,39	3,76									
1033-0	5,16	4,11									

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 15 - XX - XX - XX - 10 - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <ul style="list-style-type: none"> 01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µmTIN OVER NICKEL (RoHS) ◇ 15 0,25µm GOLD OVER NICKEL (RoHS) <p>SPECIFY CONTACT FINISH:</p> <ul style="list-style-type: none"> 02 2,54µm TIN/LEAD OVER NICKEL ◇ 84 2,54µm TIN OVER NICKEL (RoHS) ◇ 27 0,76µm GOLD OVER NICKEL (RoHS) <p>SELECT CONTACT #30 or #32 CONTACT (DATA ON PAGE 219)</p>