



Conductor size  
Ø 6 ... 8 mm / 0.14 - 0.5 mm<sup>2</sup>

## Data

### Technical data

Connection type

M12 socket

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



Pole No.	5
Connection point (shielded)	yes
Cable connection direction to mating direction	90°
Connector interface coding (cable/adapter) 1 1	A-coded

**Connection data**

Connection type (1)	Spring clamp technology
Solid conductor	0.14 ... 0.5 mm <sup>2</sup>

**Mechanical data**

Connectable sheathed cable diameter	6 ... 8 mm
Weight	70 g

**Environmental requirements**

Protection type	IP67
-----------------	------

**Commercial data**

PU (SPU)	1 Stück
Packaging type	box
Country of origin	DE
GTIN	4045454686406
Customs tariff number	85366990990

**Downloads****Documentation****Bid Text**

756-9210/060-000 X81 - Datei	2019. 2. 19.	xml 2.8 kB	Download
756-9210/060-000 doc - Datei	2017. 9. 20.	doc 24.6 kB	Download

**System Description**

IP67 Cables and Pluggable Connectors	pdf 293.9 kB	Download
--------------------------------------	-----------------	----------

Subject to changes. Please also observe the further product documentation!



## CAD/CAE-Data

### CAE data

WSCAD Universe 756-9210/060-000	<a href="#">URL</a>	<a href="#">Download</a>
WSCAD Universe 756-9210/060-000	<a href="#">URL</a>	<a href="#">Download</a>

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 756-9210/060-000 Accessories; M12 socket, right angle; 5-pole	<a href="#">URL</a>	<a href="#">Download</a>
---	---------------------	--------------------------

## Installation Notes

Subject to changes. Please also observe the further product documentation!