


| | |
|----------------------|--|
| Sales Region | Worldwide (except Japan) |
| Series | ALE |
| Model | ALE-OEM |
| Status |  Production |
| Option | Positive polarity |
| Option Lineup | Please refer to here. |
| Accessories | Please refer to the catalog |



Electrical Characteristics

| | |
|----------------------------------|---------------|
| Input | Single-phase |
| Input Voltage Range[AC] | 180 to 254Vac |
| Input Frequency Range | 47 to 63Hz |
| Rated Output Voltage[DC] | 3000Vdc |
| Output Voltage Range[DC] | 0 to 3000V |
| Average Capacitor Charging Power | 1500J/sec |
| Peak Capacitor Charging Power | 1650J/sec |
| Charge Current | 1.1A |
| Continuous DC Current | 500mA |
| Continuous DC Power | 1.5kW |
| Polarity | Positive |
| Power Factor | 0.65 |
| Efficiency | 85% Typ. |

Package Type & Size

| | |
|--------------------|---------------------------|
| Package / Mounting | Enclosed / Unit type |
| Width(W) | 146mm Nom. (5.75in Nom.) |
| Height(H) | 141mm Nom. (5.55in Nom.) |
| Depth(D) | 361mm Nom. (14.21in Nom.) |
| Weight | 4000g Typ. (8.8lbs Typ.) |

Other

| | |
|----------------------------|-------------|
| Operating Temp. Range | -20 to 45°C |
| Storage Temp. Range | -40 to 85°C |
| Cooling | Forced air |
| Safety Standard(Certified) | IEC60601-1 |
| | EN60601-1 |
| | UL60601-1 |

Safety Standard(Conformed)

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.