PD - 93793E

International
IOR Rectifier

RADIATION HARDENED POWER MOSFET THRU-HOLE (TO-39)

IRHF57Z30
JANSR2N7491T2
30V, N-CHANNEL
REF: MIL-PRF-19500/701

R5™ TECHNOLOGY

Product Summary

Part Number	Radiation Level	$R_{DS(on)}$	I_D	QPL Part Number
IRHF57Z30	100K Rads (Si)	0.045Ω	12A*	JANSR2N7491T2
IRHF53Z30	300K Rads (Si)	0.045Ω	12A*	JANSF2N7491T2
IRHF54Z30	500K Rads (Si)	0.045Ω	12A*	JANSG2N7491T2
IRHF58Z30	1000K Rads (Si)	0.056Ω	12A*	JANSH2N7491T2



TO-39

International Rectifier's R5™ technology provides high performance power MOSFETs for space applications. These devices have been characterized for Single Event Effects (SEE) with useful performance up to an LET of 80 (MeV/(mg/cm²)). The combination of low $R_{DS(on)}$ and low gate charge reduces the power losses in switching applications such as DC to DC converters and motor control. These devices retain all of the well established advantages of MOSFETs such as voltage control, fast switching, ease of paralleling and temperature stability of electrical parameters.

Features:

- Single Event Effect (SEE) Hardened
- Ultra Low $R_{DS(on)}$
- Identical Pre and Post Electrical Test Conditions
- Repetitive Avalanche Ratings
- Dynamic dv/dt Ratings
- Simple Drive Requirements
- Ease of Paralleling
- Hermetically Sealed
- Electrically Isolated

Absolute Maximum Ratings

Pre-Irradiation

	Parameter		Units
I_D @ V_{GS} = 12V, T_C = 25°C	Continuous Drain Current	12*	A
I_D @ V_{GS} = 12V, T_C = 100°C	Continuous Drain Current	10	
I_{DM}	Pulsed Drain Current ①	48	
P_D @ T_C = 25°C	Max. Power Dissipation	25	W
	Linear Derating Factor	0.2	W/°C
V_{GS}	Gate-to-Source Voltage	±20	V
E_{AS}	Single Pulse Avalanche Energy ②	520	mJ
I_{AR}	Avalanche Current ①	12	A
E_{AR}	Repetitive Avalanche Energy ①	2.5	mJ
dv/dt	Peak Diode Recovery dv/dt ③	3.0	V/ns
T_J	Operating Junction	-55 to 150	°C
T_{STG}	Storage Temperature Range		
	Lead Temperature	300 (0.063 in./1.6mm from case for 10s)	
	Weight	0.98 (Typical)	g

* Current is limited by package

For footnotes refer to the last page

Electrical Characteristics @ Tj = 25°C (Unless Otherwise Specified)

	Parameter	Min	Typ	Max	Units	Test Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	30	—	—	V	V_{GS} = 0V, I_D = 1.0mA
$\Delta BV_{DSS}/\Delta T_J$	Temperature Coefficient of Breakdown Voltage	—	0.03	—	V/°C	Reference to 25°C, I_D = 1.0mA
$R_{DS(on)}$	Static Drain-to-Source On-State Resistance	—	—	0.045	Ω	V_{GS} = 12V, I_D = 10A ④
$V_{GS(th)}$	Gate Threshold Voltage	2.0	—	4.0	V	V_{DS} = V_{GS}, I_D = 1.0mA
g_{fs}	Forward Transconductance	12	—	—	S (℧)	V_{DS} ≥ 15V, I_{DS} = 10A ④
I_{DSS}	Zero Gate Voltage Drain Current	—	—	10	μA	V_{DS}= 24V ,V_{GS}=0V
		—	—	25		V_{DS} = 24V, V_{GS} = 0V, T_J = 125°C
I_{GSS}	Gate-to-Source Leakage Forward	—	—	100	nA	V_{GS} = 20V
I_{GSS}	Gate-to-Source Leakage Reverse	—	—	-100		V_{GS} = -20V
Q_g	Total Gate Charge	—	—	65	nC	V_{GS} =12V, I_D = 12A
Q_{gs}	Gate-to-Source Charge	—	—	20		V_{DS} = 15V
Q_{gd}	Gate-to-Drain ('Miller') Charge	—	—	10		
$t_{d(on)}$	Turn-On Delay Time	—	—	25	ns	V_{DD} = 15V, I_D = 12A
t_r	Rise Time	—	—	100		V_{GS} =12V, R_G = 7.5Ω
$t_{d(off)}$	Turn-Off Delay Time	—	—	35		
t_f	Fall Time	—	—	30		
$L_S + L_D$	Total Inductance	—	7.0	—	nH	Measured from Drain lead (6mm /0.25in. from package) to Source lead (6mm /0.25in. from package) with Source wires internally bonded from Source Pin to Drain Pad
C_{iss}	Input Capacitance	—	2055	—	pF	V_{GS} = 0V, V_{DS} = 25V
C_{oss}	Output Capacitance	—	936	—		f = 1.0MHz
C_{rss}	Reverse Transfer Capacitance	—	35	—		

Source-Drain Diode Ratings and Characteristics

	Parameter	Min	Typ	Max	Units	Test Conditions
I_S	Continuous Source Current (Body Diode)	—	—	12*	A	
I_{SM}	Pulse Source Current (Body Diode) ①	—	—	48		
V_{SD}	Diode Forward Voltage	—	—	1.5	V	T_j = 25°C, I_S = 12A, V_{GS} = 0V ④
t_{rr}	Reverse Recovery Time	—	—	92	ns	T_j = 25°C, I_F = 12A, di/dt ≤100A/μs
Q_{RR}	Reverse Recovery Charge	—	—	194	nC	V_{DD} ≤ 25V ④
t_{on}	Forward Turn-On Time	Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by $L_S + L_D$.				

* Current is limited by package

Thermal Resistance

	Parameter	Min	Typ	Max	Units	Test Conditions
R_{thJC}	Junction-to-Case	—	—	5.0	°C/W	
R_{thJA}	Junction-to-Ambient	—	—	175		Typical socket mount

Note: Corresponding Spice and Saber models are available on International Rectifier web site.

For footnotes refer to the last page

International Rectifier Radiation Hardened MOSFETs are tested to verify their radiation hardness capability. The hardness assurance program at International Rectifier is comprised of two radiation environments. Every manufacturing lot is tested for total ionizing dose (per notes 5 and 6) using the TO-3 package. Both pre- and post-irradiation performance are tested and specified using the same drive circuitry and test conditions in order to provide a direct comparison.

Table 1. Electrical Characteristics @ Tj = 25°C, Post Total Dose Irradiation ⑤⑥

	Parameter	Up to 500K Rads(Si)[1]		1000K Rads (Si)[2]		Units	Test Conditions
		Min	Max	Min	Max		
BV_{DSS}	Drain-to-Source Breakdown Voltage	30	—	30	—	V	V_{GS} = 0V, I_D = 1.0mA
$V_{GS(th)}$	Gate Threshold Voltage	2.0	4.0	1.5	4.0		V_{GS} = V_{DS}, I_D = 1.0mA
I_{GSS}	Gate-to-Source Leakage Forward	—	100	—	100	nA	V_{GS} = 20V
I_{GSS}	Gate-to-Source Leakage Reverse	—	-100	—	-100		V_{GS} = -20 V
I_{DSS}	Zero Gate Voltage Drain Current	—	10	—	25	µA	V_{DS}= 24V, V_{GS} =0V
$R_{DS(on)}$	Static Drain-to-Source ④ On-State Resistance (TO-3)	—	0.024	—	0.03	Ω	V_{GS} =12V, I_D =10A
$R_{DS(on)}$	Static Drain-to-Source ④ On-State Resistance (TO-39)	—	0.045	—	0.056	Ω	V_{GS} =12V, I_D =10A
V_{SD}	Diode Forward Voltage ④	—	1.5	—	1.5	V	V_{GS} = 0V, I_S =12A

1. Part numbers IRHF57Z30 (JANSR2N7491T2), IRHF53Z30 (JANSF2N7491T2) and IRHF54Z30 (JANSG2N7491T2)
2. Part number IRHF58Z30 (JANSH2N7491T2)

International Rectifier radiation hardened MOSFETs have been characterized in heavy ion environment for Single Event Effects (SEE). Single Event Effects characterization is illustrated in Fig. a and Table 2.

Table 2. Single Event Effect Safe Operating Area

Ion	LET (MeV/(mg/cm²))	Energy (MeV)	Range (µm)	V_{DS} (V) @V_{GS}=0V	@V_{GS}=-5V	@V_{GS}=-10V	@V_{GS}=-15V	@V_{GS}=-20V
Cu	28	261	40	30	30	30	25	15
Br	37	285	37	30	30	30	23	15
I	60	344	33	25	25	20	15	8




Fig a. Single Event Effect, Safe Operating Area

For footnotes refer to the last page




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance Vs. Temperature




Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode Forward Voltage




Fig 8. Maximum Safe Operating Area




Fig 9. Maximum Drain Current Vs. Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case




Fig 12a. Unclamped Inductive Test Circuit




Fig 12c. Maximum Avalanche Energy Vs. Drain Current




Fig 12b. Unclamped Inductive Waveforms




Fig 13a. Basic Gate Charge Waveform




Fig 13b. Gate Charge Test Circuit

Footnotes:

① Repetitive Rating; Pulse width limited by maximum junction temperature.

② V_{DD} = 20V, starting T_J = 25°C, L= 7.2mH Peak I_L = 12A, V_{GS} = 12V


③ $I_{SD} \leq$ 12A, di/dt ≤ 135A/µs, $V_{DD} \leq$ 30V, $T_J \leq$ 150°C

④ Pulse width ≤ 300 µs; Duty Cycle ≤ 2%

⑤ **Total Dose Irradiation with V_{GS} Bias.** 12 volt V_{GS} applied and V_{DS} = 0 during irradiation per MIL-STD-750, method 1019, condition A.

⑥ **Total Dose Irradiation with V_{DS} Bias.** 24 volt V_{DS} applied and V_{GS} = 0 during irradiation per MIL-STD-750, method 1019, condition A.

Case Outline and Dimensions — TO-205AF (Modified TO-39)



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME 14.5M–1994.
2. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
3. CONTROLLING DIMENSION: INCH.
4. CONFORMS TO JEDEC OUTLINE TO–205AF (TO–39).

LEGEND

1- SOURCE
2- GATE
3- DRAIN

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
IR LEOMINSTER : 205 Crawford St., Leominster, Massachusetts 01453, USA Tel: (978) 534-5776
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information.
Data and specifications subject to change without notice. 04/2006