

RWS1000B-36/ME<sub>New</sub>  
Product



<b>Sales Region</b>	Worldwide
<b>Series</b>	RWS-B/ME
<b>Status</b>	Production
<b>Feature</b>	<b>Medical</b> for Medical instruments
<b>Option</b>	Approved by safety standards for medical equipment
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



Electrical Characteristics	
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 340V
Efficiency	88% Typ.
Rated Output Voltage[DC]	36V
Output Voltage Range[DC]	30.6 to 41.4V
Maximum Output Current	28A
Maximum Output Power	1008W

Cases Shape & Size	
Case'□ shape	Unit
Width(W)	127mm Nom.
Height(H)	63mm Nom.
Depth(D)	198mm Nom.
Weight	2000g Typ.

Other	
Operating Temp. Range	-20 to 60°C
Cooling	Blower fan cooling
Safety Standard(Certified)	ES60601-1 3rd Edition CSA C22.2 No.60601-1 3rd Edition EN60601-1 3rd Edition
Safety Standard(Conformed)	
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.