



SPECIFICATION FOR APPROVAL

SIG252010-XXX Sealed Choke Coil

1. Features

Low profile : 2.5mm x 2.0mm x 1.0mm

Low coil resistance with large currents.

High magnetic shield construction should actualize high resolution for EMC protection.

100% lead (Pb) free meet RoHS standard

2. Application

Cellular phones, LCD displays, HDDs, DVCs, DSCs, PDAs etc..

3. Type Designation


SIG	252010	-	XXX
(1)	(2)		(3)

Where (1) Series No :


(2) Size :
252010 = 2.5mm x 2.0mm x 1.0mm

(3) Inductance Value :
3R3 = 3.3μH

4. Outline Dimensions



Code	Dimensions (mm)
L	2.0 ± 0.1
W	2.5 ± 0.1
T	1.0 Max
P	0.4 ± 0.2




Note: This graph is only regard to dimensions spec. For outer appearance, please refer to actual product.

SPECIFICATION FOR APPROVAL

5. Recommend Land Pattern Dimensions

The customer shall determine the land dimensions shown above after confirming and safety.



A	2.1
B	0.8
C	2.6

Unit : mm

6. Specifications

Part Number	L0 Inductance (μH) @ (0A)	R_{dc} ($\text{m}\Omega$)		Heat Rating Current DC Amps. Idc (A)		Saturation Current DC Amps. Isat (A)	
		Typical	Maximum	Typical	Maximum	Typical	Maximum
SIG252010-R47	0.47	40	48	2.30	2.07	2.80	2.50
SIG252010-R50	0.50	55	66	2.10	1.89	2.70	2.43
SIG252010-1R0	1.0	71	85	1.70	1.53	2.00	1.80
SIG252010-1R5	1.5	107	128	1.40	1.26	1.70	1.50
SIG252010-2R2	2.2	158	190	1.10	0.99	1.40	1.20
SIG252010-3R3	3.3	253	304	0.94	0.84	1.20	1.00
SIG252010-4R7	4.7	367	440	0.78	0.70	0.98	0.88
SIG252010-6R8	6.8	451	541	0.70	0.63	0.82	0.74
SIG252010-100	10.0	712	854	0.52	0.46	0.65	0.59
SIG252010-220	22.0	1,716	2,059	0.30	0.27	0.35	0.31

* : If you require another part number please contact with us.

** : Inductance Tolerance $\pm 20\%$

Note 1. : All test data is referenced to 25°C ambient.

Note 2. : Idc : DC current (A) that will cause an approximate ΔT of 40°C

Note 3. : Isat : DC current (A) that will cause L_0 to drop approximately 30%

Note 4. : Operating Temperature Range -55°C to $+125^{\circ}\text{C}$

Note 5. : The part temperature (ambient + temp rise) should not exceed 125°C under worse case operating conditions. Circuit design , component placement, PWB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.

Note 6. : The rated current as listed is either the saturation current or the heating current depending on which value is lower.











SPECIFICATION FOR APPROVAL

DOCUMENT : SIG252010-XXX

REVISION : A3

PAGE : 3 OF 11

6-1 Current Characteristic





SPECIFICATION FOR APPROVAL

