Product data sheet
Characteristics

H364AWKEI
Safety switch, heavy duty, fusible, 200A, 3 poles, 150 hp, 600 VAC/DC, NEMA 12, interlock kit

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 2,906.00 USD

Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device application	Heavy application
Disconnect Type	Fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	3
Current Rating	200 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 3R/12
Maximum Horse Power Rating	50 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 125 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 60 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 150 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 40 hp 250 V at DC 50 hp 600 V at DC

Complementary

Mounting Type	Surface
Wiring configuration	3-wire
Wire Size	AWG 6...250 kcmil copper or aluminium
Tightening torque	275 lbf.in (31.07 N.m) 0.02…0.20 in² (13.3…127 mm²) (AWG 6...250 kcmil)
Depth	8.75 in (222.25 mm)
Width	18.63 in (473.20 mm)
Height	29 in (736.60 mm)

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Certifications	UL listed file E2875

Ordering and shipping details

Category	00160 - DE1 MISC
Discount Schedule	DE1
GTIN	00785901753964
Nbr. of units in pkg.	1
Package weight(Lbs)	47 lb(US) (21.32 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months