



## Screw Connectors

### 230/ 7 DS GW

Terminal Block, 7 pole, Insulating Material: PA 6-GW, Cross-Section: 2.5 mm<sup>2</sup>, Pin Spacing: 8.0 mm, Wire Protector (DS): yes, Fixing: Screw, Voltage Rating: 450 V, Current Rating: 24 A



### Order Info

<b>Reference Number (ref. no.)</b>	1213G7
<b>Applications</b>	Lighting, Installation, Electrical Appliances
<b>PU</b>	450

### Type

<b>Type</b>	Terminal Block
<b>Number of poles</b>	7 pole
<b>Clamping Units per Pole</b>	1
<b>Colour</b>	white
<b>Cross-Section</b>	2.5 mm <sup>2</sup>
<b>Connection Type</b>	Screw
<b>Wire Protector (DS)</b>	yes

### Technical Data

<b>Voltage Rating</b>	450 V
<b>Current Rating</b>	24 A
<b>Insulating Material</b>	PA 6-GW
<b>Contact Material</b>	Brass
<b>Core Cross-Section min.</b>	0.5 mm <sup>2</sup>
<b>Core Cross-Section max.</b>	2.5 mm <sup>2</sup>
<b>Flammability Rating</b>	V-2
<b>max. Ambient Temperature Operation</b>	85 °C
<b>Type of Conductor Solid</b>	yes
<b>Type of Conductor Flexible</b>	yes
<b>Type of Conductor Stranded</b>	yes
<b>Stripping Length</b>	5.0-5.5 mm
<b>Assembly Contact Screw</b>	0.8x4.0 / ⚙ 0.5 Nm
<b>Pin Spacing</b>	8.0 mm
<b>Fixing</b>	Screw
<b>Approbation EN60998</b>	200_230_EN60998_20012012_VDE_ENEC_40034813_web.pdf
<b>Approbation UL</b>	230_19820924_20120103_UL_E63492_1-02_Description_web.pdf
<b>Approbation CSA</b>	Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765

## Accessories

---

**ZEL 110**

196420

---