



	三型	四型	六型	九型
A	7.62	10.16	15.24	22.86
B	4.14	6.68	11.76	19.38
C	10.12	12.66	17.74	25.36

ELECTRICAL:
 CURRENT RATING: 3.0Amps/CONTACT MAX.
 CONTACT RESISTANCE: 20mΩ/CONTACT MAX.
 INSULATION RESISTANCE: 1000MΩ AT V=100V MIN.
 OPERATING VOLTAGE: 60V AC/DC

MECHANICAL:
 AVERAGE INSERTION FORCE WITH STEEL PIN OF Ø0.43mm: 250g MAX.
 AVERAGE WITH DRAWAL FORCE WITH STEEL PIN OF Ø0.43mm: 25G MIN.
 MECHANICAL LIFE CYCLE: 200 CYCLE MIN.
 OPERATING TEMPERATURES: GOLD PLATED: -55°C TO +125°C
 TIN PLATED: -40°C TO +105°C

SOLDERING TEMPERATURE: PBT,+240°C,10S MAX.
MATERIAL
 PIN: BRASS, MACHINED
 CLIP: BERYLLIUM COPPER OR PHOSPHOR BRONZE
 INSULATOR BODY(BLACK): PBT OR OTHER(KUL94V-0)

PART NO. Z-100 * * * * * 0 * * * * 0 * *
 LOGO
 0=NEXTRON LOGO
 1=NO LOGO

NO. OF CONTACT 06~64=06PIN~64PIN
 PLATED

DIP SPACING
 3=7.62mm
 4=10.16mm
 6=15.24mm
 9=22.86mm

HOUSING TYPE
 1=WITH BAR
 2=WITHOUT BAR (FOR 6-16PIN ONLY)

PITCH
 0=2.54mm

CODE	PIN PLATED	CLIP PLATED
1001	TIN 200u"	GOLD FLASH
1003	TIN 200u"	GOLD 10u"
1005	TIN 200u"	GOLD 30u"
1007	TIN 200u"	TIN 200u"
1301	GOLD FLASH	GOLD FLASH
1303	GOLD FLASH	GOLD 10u"
1305	GOLD FLASH	GOLD 30u"
1307	GOLD FLASH	TIN 200u"

UNITS mm □ INCH		NAME: 2.54mm IC SOCKET	
GENERAL TOLERANCES: (UNLESS SPECIFIED)		OPEN FRAME SOLDER TYPE	
mm	INCH	TITLE: CUSTOMER DWG	
4 PLACE ±.***	±.***	NEXTRONICS ENGINEERING CORP.	
3 PLACE ±.***	±.***	PART NO: Z-100*****0*	
2 PLACE ±.010 ±.***	±.010 ±.***	APPD: 楊海文	DWG NO: 010-0000-633
1 PLACE ±.030 ±.***	±.030 ±.***	CHKD: 廖小瓊	C
ANGULAR: X°±1° Y'±**	X'±**	DRAWN: 陳惠枝	SCALE: SHEET: REV.:
		DATE	1/1 1/1 B
B PART NO MODIFY Δ=2	3/11/16		
A1 PART NO MODIFY	8/17/11		
A NEW RELEASED	10/28/09		
REV.	DESCRIPTION		

正源精密工业(广东)有限公司
 2016/3/18
 内部资料请勿复印