



Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull in	at 20 °C	4,5		10	mm
Drop out	at 20 °C	5,5		13,5	mm
Test equipment				SV 002	

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - form			A - NO		
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
operating voltage	DC or Peak AC			180	VDC
operating ampere	DC or Peak AC			1,25	A
Switching current	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive			390	mOhm
Housing material			PBT glass fibre reinforced		
Case color			blue		
Sealing compound			Polyurethan		

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	cable not moved	-30		80	°C
Operating temperature	cable moved	-5		80	°C
Storage temperature		-30		80	°C

Cable specification	Conditions	Min	Typ	Max	Unit
Cable typ			round cable		
Cable material			PVC		
Cross section			0,25 gmm		

General data	Conditions	Min	Typ	Max	Unit
Mounting advice			over 5m cable, a series resistor is recommended.		
mounting advice 1			Decreased switching distances by mounting on iron		
mounting advice 2			Magnetically conductive screws must not be used		
tightening torque	Screw M3 ISO 1207 Disk ISO 7089			0,5	Nm