


Silicon NPN Epitaxial Planar Type

2SD875

■ Features

- Large collector power dissipation P_C .
- High collector-emitter voltage (Base open) V_{CEO} .
- Mini power type package, allowing downsizing of the equipment and automatic insertion through the tape packing and the magazine packing.

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Collector-base voltage	V_{CBO}	80	V
Collector-emitter voltage	V_{CEO}	80	V
Emitter-base voltage	V_{EBO}	5	V
Collector current	I_C	0.5	A
Peak collector current	I_{CP}	1	A
Collector power dissipation	P_C	1	W
Junction temperature	T_j	150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +150	$^\circ\text{C}$

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base voltage	V_{CBO}	$I_C = 10\ \mu\text{A}$, $I_E = 0$	80			V
Collector-emitter voltage	V_{CEO}	$I_C = 100\ \mu\text{A}$, $I_B = 0$	80			V
Emitter-base voltage	V_{EBO}	$I_E = 10\ \mu\text{A}$, $I_C = 0$	5			V
Collector-base cutoff current	I_{CBO}	$V_{CB} = 20\ \text{V}$, $I_B = 0$			0.1	μA
Forward current transfer ratio	h_{FE}	$V_{CE} = 10\ \text{V}$, $I_C = 150\ \text{mA}$	130		330	?
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 300\ \text{mA}$, $I_B = 30\ \text{mA}$		0.2	0.4	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = 300\ \text{mA}$, $I_B = 30\ \text{mA}$		0.85	1.2	V
Transition frequency	f_T	$V_{CB} = 10\ \text{V}$, $I_E = -50\ \text{mA}$, $f = 200\ \text{MHz}$		120		MHz
Collector output capacitance	C_{ob}	$V_{CB} = 10\ \text{V}$, $I_E = 0$, $f = 1\ \text{MHz}$		11	20	pF

■ h_{FE} Classification

Marking	X	
Rank	R	S
h_{FE}	130~220	185~330