

International  
**IOR** Rectifier

## ST280S SERIES

### PHASE CONTROL THYRISTORS

Stud Version

#### Features

- Center amplifying gate
- Hermetic metal case with glass-metal seal insulator
- International standard case TO-209AB (TO-93)
- Compression Bonded Encapsulation for heavy duty operations such as severe thermal cycling


280A

#### Typical Applications

- DC motor controls
- Controlled DC power supplies
- AC controllers

#### Major Ratings and Characteristics

| Parameters        | ST280S      | Units             |
|-------------------|-------------|-------------------|
| $I_{T(AV)}$       | 280         | A                 |
| @ $T_C$           | 85          | °C                |
| $I_{T(RMS)}$      | 440         | A                 |
| $I_{TSM}$ @ 50Hz  | 7850        | A                 |
| @ 60Hz            | 8220        | A                 |
| $I^2t$ @ 50Hz     | 308         | KA <sup>2</sup> s |
| @ 60Hz            | 281         | KA <sup>2</sup> s |
| $V_{DRM}/V_{RRM}$ | 400 to 600  | V                 |
| $t_q$ typical     | 100         | μs                |
| $T_J$             | - 40 to 125 | °C                |



## ST280S Series

Bulletin I25161 rev. C 03/03

International  
**IRF** Rectifier

### ELECTRICAL SPECIFICATIONS

#### Voltage Ratings

| Type number | Voltage Code | $V_{DRM}/V_{RRM}$ , max. repetitive peak and off-state voltage<br>V | $V_{RSM}$ , maximum non-repetitive peak voltage<br>V | $I_{DRM}/I_{RRM}$ max.<br>@ $T_J = T_J \text{ max}$<br>mA |
|-------------|--------------|---------------------------------------------------------------------|------------------------------------------------------|-----------------------------------------------------------|
| ST280S      | 04           | 400                                                                 | 500                                                  | 30                                                        |
|             | 06           | 600                                                                 | 700                                                  |                                                           |

#### On-state Conduction

| Parameter                                                    | ST280S     | Units              | Conditions                                                                                |
|--------------------------------------------------------------|------------|--------------------|-------------------------------------------------------------------------------------------|
| $I_{T(AV)}$ Max. average on-state current @ Case temperature | 280        | A                  | 180° conduction, half sine wave                                                           |
|                                                              | 85         | °C                 |                                                                                           |
| $I_{T(RMS)}$ Max. RMS on-state current                       | 440        | A                  | DC @ 75°C case temperature                                                                |
| $I_{TSM}$ Max. peak, one-cycle non-repetitive surge current  | 7850       | A                  | t = 10ms No voltage reappplied                                                            |
|                                                              | 8220       |                    | t = 8.3ms reappplied                                                                      |
|                                                              | 6600       |                    | t = 10ms 100% $V_{RRM}$                                                                   |
|                                                              | 6900       |                    | t = 8.3ms reappplied                                                                      |
| $I^2t$ Maximum $I^2t$ for fusing                             | 310        | KA <sup>2</sup> s  | t = 10ms No voltage reappplied                                                            |
|                                                              | 220        |                    | t = 8.3ms reappplied                                                                      |
|                                                              | 218        |                    | t = 10ms 100% $V_{RRM}$                                                                   |
|                                                              | 200        |                    | t = 8.3ms reappplied                                                                      |
| $I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing               | 3100       | KA <sup>2</sup> √s | t = 0.1 to 10ms, no voltage reappplied                                                    |
| $V_{T(TO)1}$ Low level value of threshold voltage            | 0.84       | V                  | $(16.7\% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}), T_J = T_J \text{ max.}$ |
| $V_{T(TO)2}$ High level value of threshold voltage           | 0.88       |                    | $(I > \pi \times I_{T(AV)}), T_J = T_J \text{ max.}$                                      |
| $r_{t1}$ Low level value of on-state slope resistance        | 0.50       | mΩ                 | $(16.7\% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}), T_J = T_J \text{ max.}$ |
| $r_{t2}$ High level value of on-state slope resistance       | 0.47       |                    | $(I > \pi \times I_{T(AV)}), T_J = T_J \text{ max.}$                                      |
| $V_{TM}$ Max. on-state voltage                               | 1.28       | V                  | $I_{pk} = 880A, T_J = T_J \text{ max, } t_p = 10ms$ sine pulse                            |
| $I_H$ Maximum holding current                                | 600        | mA                 | $T_J = 25^\circ C$ , anode supply 12V resistive load                                      |
| $I_L$ Max. (typical) latching current                        | 1000 (300) |                    |                                                                                           |

#### Switching

| Parameter                                                     | ST280S | Units | Conditions                                                                                                                                |
|---------------------------------------------------------------|--------|-------|-------------------------------------------------------------------------------------------------------------------------------------------|
| $di/dt$ Max. non-repetitive rate of rise of turned-on current | 1000   | A/μs  | Gate drive 20V, 20Ω, $t_f \leq 1\mu s$<br>$T_J = T_J \text{ max, anode voltage} \leq 80\% V_{DRM}$                                        |
| $t_d$ Typical delay time                                      | 1.0    | μs    | Gate current 1A, $di_g/dt = 1A/\mu s$<br>$V_d = 0.67\% V_{DRM}, T_J = 25^\circ C$                                                         |
| $t_q$ Typical turn-off time                                   | 100    |       | $I_{TM} = 300A, T_J = T_J \text{ max, } di/dt = 20A/\mu s, V_R = 50V$<br>$dv/dt = 20V/\mu s, \text{ Gate } 0V, 100\Omega, t_p = 500\mu s$ |

#### Blocking

| Parameter                                                              | ST280S | Units      | Conditions                                       |
|------------------------------------------------------------------------|--------|------------|--------------------------------------------------|
| $dv/dt$ Maximum critical rate of rise of off-state voltage             | 500    | V/ $\mu$ s | $T_J = T_J$ max linear to 80% rated $V_{DRM}$    |
| $I_{DRM}$<br>$I_{RRM}$ Max. peak reverse and off-state leakage current | 30     | mA         | $T_J = T_J$ max, rated $V_{DRM}/V_{RRM}$ applied |

#### Triggering

| Parameter                                    | ST280S      | Units | Conditions                                                                                                                                                                                          |
|----------------------------------------------|-------------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| $P_{GM}$ Maximum peak gate power             | 10.0        | W     | $T_J = T_J$ max, $t_p \leq 5ms$                                                                                                                                                                     |
| $P_{G(AV)}$ Maximum average gate power       | 2.0         |       | $T_J = T_J$ max, $f = 50Hz$ , $d\% = 50$                                                                                                                                                            |
| $I_{GM}$ Max. peak positive gate current     | 3.0         | A     | $T_J = T_J$ max, $t_p \leq 5ms$                                                                                                                                                                     |
| $+V_{GM}$ Maximum peak positive gate voltage | 20          | V     | $T_J = T_J$ max, $t_p \leq 5ms$                                                                                                                                                                     |
| $-V_{GM}$ Maximum peak negative gate voltage | 5.0         |       |                                                                                                                                                                                                     |
| $I_{GT}$ DC gate current required to trigger | TYP. 180    | mA    | $T_J = -40^\circ C$<br>$T_J = 25^\circ C$<br>$T_J = 125^\circ C$<br><br>Max. required gate trigger/ current/ voltage are the lowest value which will trigger all units 12V anode-to-cathode applied |
|                                              | MAX. -      |       |                                                                                                                                                                                                     |
|                                              | 90 150 40 - |       |                                                                                                                                                                                                     |
| $V_{GT}$ DC gate voltage required to trigger | 2.9         | V     | $T_J = -40^\circ C$<br>$T_J = 25^\circ C$<br>$T_J = 125^\circ C$                                                                                                                                    |
|                                              | 1.8 3.0     |       |                                                                                                                                                                                                     |
|                                              | 1.2 -       |       |                                                                                                                                                                                                     |
| $I_{GD}$ DC gate current not to trigger      | 10          | mA    | $T_J = T_J$ max<br>Max. gate current/ voltage not to trigger is the max. value which will not trigger any unit with rated $V_{DRM}$ anode-to-cathode applied                                        |
| $V_{GD}$ DC gate voltage not to trigger      | 0.25        | V     |                                                                                                                                                                                                     |

#### Thermal and Mechanical Specification

| Parameter                                            | ST280S             | Units       | Conditions                                 |
|------------------------------------------------------|--------------------|-------------|--------------------------------------------|
| $T_J$ Max. operating temperature range               | -40 to 125         | $^\circ C$  |                                            |
| $T_{stg}$ Max. storage temperature range             | -40 to 150         |             |                                            |
| $R_{thJC}$ Max. thermal resistance, junction to case | 0.105              | K/W         | DC operation                               |
| $R_{thCS}$ Max. thermal resistance, case to heatsink | 0.04               |             | Mounting surface, smooth, flat and greased |
| T Mounting torque, $\pm 10\%$                        | 31 (275)           | Nm (lbf-in) | Non lubricated threads                     |
|                                                      | 24.5 (210)         |             | Lubricated threads                         |
| wt Approximate weight                                | 280                | g           |                                            |
| Case style                                           | TO - 209AB (TO-93) |             | See Outline Table                          |

ST280S Series

Bulletin I25161 rev. C 03/03

$\Delta R_{thJC}$  Conduction

(The following table shows the increment of thermal resistance  $R_{thJC}$  when devices operate at different conduction angles than DC)

| Conduction angle | Sinusoidal conduction | Rectangular conduction | Units | Conditions               |
|------------------|-----------------------|------------------------|-------|--------------------------|
| 180°             | 0.016                 | 0.012                  | K/W   | $T_J = T_J \text{ max.}$ |
| 120°             | 0.019                 | 0.020                  |       |                          |
| 90°              | 0.025                 | 0.027                  |       |                          |
| 60°              | 0.036                 | 0.037                  |       |                          |
| 30°              | 0.060                 | 0.060                  |       |                          |

Ordering Information Table

Device Code

|    |    |   |   |    |   |   |   |
|----|----|---|---|----|---|---|---|
| ST | 28 | 0 | S | 06 | P | 0 | V |
| 1  | 2  | 3 | 4 | 5  | 6 | 7 | 8 |

- 1 - Thyristor
- 2 - Essential part number
- 3 - 0 = Converter grade
- 4 - S = Compression bonding Stud
- 5 - Voltage code: Code x 100 =  $V_{RRM}$  (See Voltage Rating Table)
- 6 - P = Stud base 3/4"-16UNF-2A threads
- 7 - 0 = Eyelet terminals (Gate and Auxiliary Cathode Leads)  
1 = Fast - on terminals (Gate and Auxiliary Cathode Leads)
- 8 - V = Glass-metal seal

NOTE: For Metric Device M16 x 1.5 Contact Factory

Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-state Power Loss Characteristics




Fig. 4 - On-state Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-state Voltage Drop Characteristics




Fig. 8 - Thermal Impedance  $Z_{thJC}$  Characteristic




Fig. 9 - Gate Characteristics

## ST280S Series

Bulletin I25161 rev. C 03/03

International  
**IOR** Rectifier

Data and specifications subject to change without notice.  
This product has been designed and qualified for Industrial Level.  
Qualification Standards can be found on IR's Web site.

International  
**IOR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7309  
Visit us at [www.irf.com](http://www.irf.com) for sales contact information. 03/03