


5.0A SURFACE MOUNT SCHOTTKY BARRIER DIODE
Features

- Schottky Barrier Chip
- Ideally Suited for Automatic Assembly
- Low Power Loss, High Efficiency
- Surge Overload Rating to 1.5 0A Peak
- For Use in Low Voltage Application
- Guard Ring Die Construction
- Plastic Case Material has UL Flammability Classification Rating 94V-O


Mechanical Data

- Case: SMAF, Molded Plastic
- Terminals: Solder Plated, Solderable per MIL-STD-750, Method 2026
- Polarity: Cathode Band or Cathode Notch
- Marking: Type Number
- Weight: 0.037 grams (approx.)
- **Lead Free: For RoHS / Lead Free Version**

SMAF		
Dim	Min	Max
A	3.20	3.60
B	2.40	2.80
C	1.38	1.43
D	0.10	0.20
E	4.40	4.80
F	0.90	1.10
G	0.90	-
All Dimensions in mm		

Maximum Ratings and Electrical Characteristics @T_A=25°C unless otherwise specified

Characteristic	Symbol	SS52F	SS53F	SS54F	SS55F	SS56F	SS58F	SS510F	SS515F	SS520F	Unit	
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V _{RRM} V _{VRM} V _R	20	30	40	50	60	80	100	150	200	V	
RMS Reverse Voltage	V _{R(RMS)}	14	21	28	35	42	56	70	105	140	V	
Average Rectified Output Current @T _L = 75°C	I _O	5.0									A	
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	150									A	
Forward Voltage @I _F = 5.0A	V _{FM}	0.55			0.70		0.85		0.95		V	
Peak Reverse Current @T _A = 25°C At Rated DC Blocking Voltage @T _A = 100°C	I _{RM}	0.5 20									mA	
Typical Thermal Resistance (Note 1)	R _{θJL} R _{θJA}	28 88									°C/W	
Typical Junction Capacitance	C _j	800					500					pF
Operating Temperature Range	T _j	-65 to +125									°C	
Storage Temperature Range	T _{STG}	-65 to +150									°C	

Note: 1. Mounted on P.C. Board with 5.0mm² copper pad area.




Fig. 1 Forward Current Derating Curve




Fig. 2 Typ. Forward Characteristics




Fig. 3 Max Non-Repetitive Peak Fwd Surge Current




Fig. 4 Typical Junction Capacitance




Fig. 5 Typical Reverse Characteristics