GM162

P-CHANNEL ENHANCEMENT MODE POWER MOSFET

BV_{DSS}	-30V
$R_{DS(ON)}$	80mΩ
I_D	-3.2A

Description

The GM162 provides the designer with the best combination of fast switching, low on-resistance and cost-effectiveness.

Features

- Lower on-resistance
- Ultra high-speed switching

Applications

- Notebook PCs
- Cellular and portable phones
- On-board power supplies
- Li-ion battery Systems



Package Dimensions





REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	4.4	4.6	G	3.00 REF.	
B	4.05	4.25	H	1.50 REF.	
C	1.50	1.70	I	0.40	0.52
D	1.30	1.50	J	1.40	1.60
E	2.40	2.60	K	0.35	0.41
F	0.89	1.20	L	5° TYP.	
			M	0.70 REF.	

Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	±12	V
Continuous Drain Current[3]	I_D @Ta=25℃	-3.2	A
Continuous Drain Current[3]	I_D @Ta=70℃	-2.6	A
Pulsed Drain Current[1,2]	I_{DM}	-10	A
Power Dissipation	P_D@Ta=25℃	2	W
Operating Junction and Storage Temperature Range	Tj, Tstg	-55 ~ +150	℃
Linear Derating Factor		0.01	W/℃

Thermal Data

Parameter		Symbol	Ratings	Unit
Thermal Resistance Junction-ambient[3]	**Max.**	Rthj-amb	90	℃/W

Electrical Characteristics(Tj = 25℃ Unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	BV_{DSS}	-30	-	-	V	V_{GS}=0, I_D=-250uA
Breakdown Voltage Temperature Coefficient	$\triangle BV_{DSS}/\triangle Tj$	-	-0.1	-	V/℃	Reference to 25℃, I_D=-1mA
Gate Threshold Voltage	$V_{GS(th)}$	-0.5	-	-1.2	V	V_{DS}= V_{GS}, I_D=-250uA
Forward Transconductance	gfs	-	9	-	S	V_{DS}=-5.0V ,I_D=-3.0A
Gate-Source Leakage Current	I_{GSS}	-	-	±100	nA	V_{GS}= ±12V
Drain-Source Leakage Current(Tj=25℃)	I_{DSS}	-	-	-1	uA	V_{DS}=-30V, V_{GS}=0
Drain-Source Leakage Current(Tj=70℃)		-	-	-25	uA	V_{DS}=-24V, V_{GS}=0
Static Drain-Source On-Resistance[2]	$R_{DS(ON)}$	-	-	60	mΩ	I_D=-3.2A, V_{GS}=-10V
		-	-	80		I_D=-3.0A, V_{GS}=-4.5V
		-	-	150		I_D=-2.0A, V_{GS}=-2.5V
Total Gate Charge[2]	Q_g	-	10	18	nC	I_D=-3.2A
Gate-Source Charge	Q_{gs}	-	1.8	-		V_{DS}=-24V
Gate-Drain ("Miller") Change	Q_{gd}	-	3.6	-		V_{GS}=-4.5V
Turn-on Delay Time[2]	$T_{d(on)}$	-	7	-	ns	V_{DS}=-15V I_D=-3.2A V_{GS}=-10V R_G=3.3Ω R_D=4.6Ω
Rise Time	T_r	-	15	-		
Turn-off Delay Time	$T_{d(off)}$	-	21	-		
Fall Time	T_f	-	15	-		
Input Capacitance	C_{iss}	-	735	1325	pF	V_{GS}=0V V_{DS}=-25V f=1.0MHz
Output Capacitance	C_{oss}	-	100	-		
Reverse Transfer Capacitance	C_{rss}	-	80	-		

Source-Drain Diode

Forward On Voltage[2]	V_{SD}	-	-	-1.2	V	I_S=-1.2A, V_{GS}=0
Reverse Recovery Time	T_{rr}	-	24	-	ns	I_S=-3.2A, V_{GS}=0 dI/dt=100A/μs
Reverse Recovery Charge	Q_{rr}	-	19	-	nC	

Notes: 1. Pulse width limited by Max. junction temperature.
2. Pulse width≦300us, duty cycle≦2%.
3. Surface mounted on 1 in^2 copper pad of FR4 board;270℃/w when mounted on min. copper pad.

Characteristics Curve



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. On-Resistance v.s. Gate Voltage



Fig 4. Normalized On-Resistance



Fig 5. Forward Characteristic of Reverse Diode



Fig 6. Gate Threshold Voltage v.s. Junction Temperature



Fig 7. Gate Charge Characteristics



Fig 8. Typical Capacitance Characteristics



Fig 9. Maximum Safe Operating Area



Fig 10. Effective Transient Thermal Impedance



Fig 11. Switching Time Waveform



Fig 12. Gate Charge Waveform

Important Notice:
- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:
- **Taiwan**: No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
  TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China**: (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
  TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165