

Accessories - ICC-MT 0,5-1,0 - 3190577

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Module male contact, is inserted into the ICC connector shell after the conductor has been crimped, for conductors from 0.5-1.0 mm²



Key commercial data

| | |
|------------------------|---|
| Packing unit | 1 |
| Minimum order quantity | 100 |
| Catalog page | Page 851 (CC-2011) |
| GTIN |  4 017918 093402 |
| Custom tariff number | 85389099 |
| Country of origin | GERMANY |

Technical data

Technical data

| | |
|--|---|
| Nominal current | 12 A (with 1 mm ² conductor cross section) |
| Conductor cross section stranded min. | 0.5 mm ² |
| Max. conductor cross section, stranded | 1 mm ² |

Connection data

| | |
|--------------------------------------|--------------------|
| Core diameter including insulation | 1.4 mm ... 2.31 mm |
| Stripping length of individual wires | 3.5 mm |

Classifications

eclass

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |

Accessories - ICC-MT 0,5-1,0 - 3190577

Classifications

etim

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002498 |

unspsc

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211810 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

Approvals

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Approval details



Drawings

Dimensioned drawing

