
Technical Data Sheet		Rosenberger
7-16	Calibration Kit Jack	**60K34R-MSON3**





All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to IEC 61169-4, EN 122190, DIN 47223

Documents

This kit is delivered with

- **Standard Definitions Card**
  Printed Standard Definitions that can be used on nearly all Vector Network Analyzers
- **Lanyard**
- **Hard Shell Case**

Material and plating

Connector parts	**Material**	**Plating**
Center conductor	CuBe	Gold, min. 1.27 µm, over nickel
Outer conductor	Brass	Flash white bronze over silver(e.g. Optargen®)
Body	Brass	powder coated
Dielectric	PP	
Substrate	Al_2O_3	

Dieses Dokument ist urheberrechtlich geschützt ● This document is protected by copyright ● Rosenberger Hochfrequenztechnik GmbH & Co. KG

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O.Box 1260 D-84526 Tittmoning Germany
www.rosenberger.de

Tel. : +49 8684 18-0
Email : info@rosenberger.de

Electrical data

Frequency range	DC to 4 GHz

Open

Return loss	≤ 0.15 dB, DC to 4 GHz
Error from nominal phase[1]	≤ 3.0°, DC to 4 GHz

Short

Return loss	≤ 0.15 dB, DC to 4 GHz
Error from nominal phase[2]	≤ 3.0°, DC to 4 GHz

Load

Return loss	≥ 40 dB, DC to 2.5 GHz ≥ 38 dB, 2.5 GHz to 4 GHz
DC-Resistance	50 Ω ± 0.5 Ω
Power handling	≤ 1.0 W

[1] The nominal phase is defined by the Offset Delay, the Offset Loss and the Fringing Capacitances
[2] The nominal phase is defined by the Offset Delay, the Offset Loss and the Short Inductance

Mechanical data

Mating cycles	≥ 500
Maximum torque	30 Nm
Recommended torque	2.26 Nm
Gauge	1.77 mm to 2.07 mm

General standard definitions

For proper operation the vector network analyzer (VNA) needs a model describing the electrical behaviour of this calibration standard. The different models, units, and terms used will depend on the VNA type and they will have to be entered into the VNA. All values are based on typical geometry and plating.

Open

Offset Z_0 / Impedance / Z_0	50 Ω		
Offset Delay	87.394 ps		
Length (electrical) / Offset Length	26.20 mm		
Offset Loss	0.50 GΩ/s		
Loss	0.0076 dB/$\sqrt{\text{GHz}}$		
Fringing Capacitances	C_0 =	177.000 x 10^{-15} F	/ 177.000 fF
	C_1 =	7200.00 x 10^{-27} F/Hz	/ 7.20000 fF /GHz
	C_2 =	-3300.00 x 10^{-36} F/Hz^2	/ -3.30000 fF /GHz^2
	C_3 =	386.000 x 10^{-45} F/Hz^3	/ 0.38600 fF /GHz^3

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O.Box 1260 D-84526 Tittmoning Germany
www.rosenberger.de

Tel. : +49 8684 18-0
Email : info@rosenberger.de

Short

Offset Z_0 / Impedance / Z_0	50 Ω		
Offset Delay	96.734 ps		
Length (electrical) / Offset Length	29.00 mm		
Offset Loss	0.50 GΩ/s		
Loss	0.0084 dB/$\sqrt{GHz}$		
Short Inductance	$L_0 = 0.0000 \times 10^{-12}$ H	/	0.0000 pH
	$L_1 = 0.0000 \times 10^{-24}$ H/Hz	/	0.0000 pH/GHz
	$L_2 = 0.0000 \times 10^{-33}$ H/Hz^2	/	0.0000 pH/GHz^2
	$L_3 = 0.0000 \times 10^{-42}$ H/Hz^3	/	0.0000 pH/GHz^3

Load

Offset Z_0 / Impedance / Z_0	50 Ω
Offset Delay	0.0000 ps
Length (electrical) / Offset Length	0.000 mm
Offset Loss	0.00 GΩ/s
Loss	0.0000 dB/$\sqrt{GHz}$

Environmental data

Operating temperature range[3]	0 °C to +50 °C
Storage temperature range	- 55 °C to +90 °C
RoHS	compliant

[3] *Temperature range over which these specifications are valid.*

Packing

Standard	1 pce in bag
Weight	310 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O.Box 1260 D-84526 Tittmoning Germany
www.rosenberger.de

Tel. : +49 8684 18-0
Email : info@rosenberger.de

Dieses Dokument ist urheberrechtlich geschützt ● This document is protected by copyright ● Rosenberger Hochfrequenztechnik GmbH & Co. KG