


ZWS150BP-24/L



<b>Sales Region</b>	Worldwide
<b>Series</b>	ZWS-BP
<b>Status</b>	Production
<b>Feature</b>	Peak power capability
<b>Option</b>	With chassis model
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	90% Typ.
Rated Output Voltage[DC]	24V
Output Voltage Range[DC]	21.6 to 27.5V
Maximum Output Current	
Maximum Average Current	6.3A
Maximum Peak Current	12.6A
Maximum Output Power	
Maximum Average Power	151.2W
Maximum Peak Power	302.4W

### Cases Shape & Size

Case'□ shape	PC board
Width(W)	85mm Nom.
Height(H)	47mm Nom.
Depth(D)	188mm Nom.
Weight	530g Typ.

### Other

Operating Temp. Range	-10 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
Safety Standard(Conformed)	EN50178 (OV II)
	Den-an

*! Images are for reference only and show exemplary products.*

**Remarks** ! This PDF document was created based on the data listed on the TDK Corporation website. All specifications are subject to change without notice. This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.