

CC1V-T1A

Tuning Fork Crystal 10 kHz – 2.1 MHz




100% leadfree, RoHS - compliant

Small SMT ceramic package
Package height 1.75 mm
SMD-package in Tape and Reel
Ind. and Ext. temperature ranges
High stability
Low aging
Low power consumption
High shock and vibration resistance


ELECTRICAL CHARACTERISTICS AT 25°C:

DIMENSIONS

Package:



Recommended Solder Pad:



All dimensions in mm typical

DESCRIPTION:

In the range between 10 and 200 kHz, the tuning fork resonators vibrate in the fundamental mode. From 201 to 560 kHz, an overtone mode is used. The frequency range from 561 kHz to 2.1 MHz is covered with length extensional resonators.

The crystals are supplied in special trays (100 crystals per tray).

For pick-and-place equipment, the parts are available in 16 mm tape:

7" (178 mm) reel with 1'000 crystals

10" (254 mm) reel with 2'000 crystals

13" (330 mm) reel with 4'000 crystals

Frequency Range	F _L	10–200	201–560	561–2'100	kHz
Load capacitance ¹⁾	C _L	9.0 / 12.5	4.0	10.0	pF
Frequency tolerance ²⁾	ΔF/F	+/-30	+/-100	+/-100	ppm
	ΔF/F	+/-100	+/-250	+/-500	ppm
Drive level max.	P	1.0		μW	
Insulation resistance min.	R _i	500		MΩ	
Aging first year max.	ΔF/F	+/-3		ppm	

Frequency Example ³⁾	F _L	32.768	307.200	1'000	kHz
Series resistance typ./max.	R _S	37 / 60	1.4 / 3.5	0.6 / 1.2	kΩ
Motional capacitance typ.	C ₁	2.1	1.7	1.4	fF
Static capacitance typ.	C ₀	1.6	1.6	1.2	pF
Turnover temperature	T ₀	25 +/-5	22 +/-5	39 +/-5	°C
Frequency vs. temperature	ΔF/F ₀	-0.035 ppm/°C ² (T - T ₀) ² +/-10%		ppm	

1) Other load capacitances on request.

2) Tighter and wider frequency tolerances on request.

3) Values for other frequencies consult factory.

STANDARD FREQUENCIES:


Frequency kHz					Frequency MHz
10.000	12.800	16.000	16.384	20.480	1.0000
31.200	32.000	32.768	38.400	40.000	1.2288
40.960	60.000	75.000	76.800	100.000	1.8432
128.000	153.600	240.000	307.200	455.000	2.0000
768.000					
Other frequencies between 10 kHz and 2.1 MHz on request					

**ENVIRONMENTAL
CHARACTERISTICS:**

		Conditions	Max. Dev.
Storage temp. range		-55 to +125°C	
Industrial operating temp. range		-40 to +85°C	
Extended operating temp. range		-55 to +125°C	
Shock resistance	ΔF/F	5000 g, 0.3 ms, ½ sine	+/-5 ppm
Vibration resistance	ΔF/F	20 g / 10–2000 Hz	+/-5 ppm

**TERMINATIONS AND
PROCESSING:**

Type	Termination	Processing
CC1V-T1A	For SMD mounting Au flashed pads	Reflow soldering 260°C / 20 s max.

**PART NUMBER/
ORDERING INFORMATION
EXAMPLE:**


All specifications subject to change without notice. 05.07



A COMPANY OF THE SWATCH GROUP

Micro Crystal
Div. of ETA SA
Mühlestrasse 14
CH-2540 Grenchen
Switzerland

Tel. +41 32 655 82 82
Fax +41 32 655 82 83
sales@microcrystal.ch
www.microcrystal.com

Version 5.1/05.2007