


Red LED L9907

AlGaInP resonant cavity LED for POF data communication



Features

- High-speed response: 70 MHz
- Optical output power: 1.1 mW
- Emission area diameter: 100 μm
- Stable optical output with low temperature dependence:
85 °C/25 °C=70 %

Applications

- POF (Plastic Optical Fiber) communication
- Light source for optical switches

■ Absolute maximum ratings


Parameter	Symbol	Value	Unit
Reverse voltage	VR Max.	3	V
Forward current	IF	50	mA
Pulsed forward current *	IFP	100	mA
Operating temperature	Topr	-30 to +85	°C
Storage temperature	Tstg	-45 to +125	°C

* Pulse width=1 μs , duty ratio 50 %

■ Electrical and optical characteristics (Ta=25 °C)


Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Peak emission wavelength	λ_p	IF=20 mA	640	660	670	nm
Spectral half width	$\Delta\lambda$	IF=20 mA	-	10	20	nm
Radiant flux	ϕ_e	IF=20 mA	0.8	1.1	-	mW
Forward voltage	VF	IF=20 mA	-	1.9	2.4	V
Cut-off frequency	fc	IF=20 mA \pm 1 mAp-p	60	70	-	MHz
Optical output ratio at different temperatures	dP/dTj	IF=20 mA, 85 °C/25 °C	-	70	-	%

■ Emission spectrum




KLEDB0264EA

■ Radiant flux vs. forward current




KLEDB0265EA

■ Forward current vs. forward voltage




KLEDB0267EA

■ Directivity




KLEDB0301EA

■ Radiant output vs. ambient temperature




KLEDB0266EA

■ Allowable forward current vs. ambient temperature



KLEDB0027EB

■ Dimensional outline (unit: mm)



KLEDA0073EA

HAMAMATSU

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2006 Hamamatsu Photonics K.K.

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184, www.hamamatsu.com

U.S.A.: Hamamatsu Corporation, 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH, Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Traipu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited, 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB, Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

Cat. No. KLED1046E04
Jun. 2006 DN