



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, CA 90638-5223

Phone: (562) 404-4474 * Fax: (562) 404-1773


ssdi@ssdi-power.com * www.ssdi-power.com

SSR05C120 Series

Designer's Data Sheet

Part Number / Ordering Information ^{1/}

SSR05C



5 A / 1200 V Schottky Silicon Carbide Rectifier

FEATURES:


- 1200 Volt Silicon Carbide Schottky Rectifier
- Average Output Current 5 Amps
- No Reverse Recovery
- No Forward Recovery
- No Switching Time Change Over Temperature
- Small Package Size
- TX, TXV, and Space Level Screening Available. Consult Factory.

MAXIMUM RATINGS

		Symbol	Value	Units
Peak Repetitive and Peak Reverse Voltage	SSR05C100 SSR05C120	V_{RRM} V_R	1000 1200	Volts
Average Rectified Forward Current (Resistive Load, 60 Hz, Sine Wave)		I_O	5	Amps
Peak Surge Current (8.3 ms Pulse, Half Sine Wave, $T_A = 25^\circ\text{C}$)		I_{FSM}	30	Amps
Operating & Storage Temperature		$T_{OP} \& T_{stg}$	-55 to +250	$^\circ\text{C}$
Junction Temperature		T_J	-55 to +250	$^\circ\text{C}$
Maximum Thermal Resistance (Junction to Case)		$R_{\theta JC}$	3.0	$^\circ\text{C/W}$


CERPACK (G) ^{2/}

Drawing# 60-0149-366




SMD .5 (S.5) ^{2/}

Drawing# 60-0149-507



LEADED CERPACK (GL) ^{2/}

Drawing# 60-0149-366-1



NOTE: All specifications are subject to change without notification.
 SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: SH0030G

DOC



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, CA 90638-5223

Phone: (562) 404-4474 * Fax: (562) 404-1773

ssdi@ssdi-power.com * www.ssdi-power.com

SSR05C120 Series

ELECTRICAL CHARACTERISTICS ^{3/}		Symbol	Min	Typ	Max	Units
Instantaneous Forward Voltage Drop (T _A =25°C, 300 - 500 μsec pulse)	I _F = 2.0 A	V _{F1}	—	1.24	1.30	V _{DC}
	I _F = 5.0 A	V _{F2}	—	1.65	1.80	V _{DC}
Instantaneous Forward Voltage Drop (300 - 500 μsec pulse)	T _A = -55°C, I _F = 5 A	V _{F4}	—	1.48	1.52	V _{DC}
	T _A = 150 °C, I _F = 5 A	V _{F5}	—	2.80	3.00	V _{DC}
Reverse Leakage Current (Rated V _R , T _A = 25°C, 300 μsec pulse minimum)		I _{R1}	—	2	100	μA
Reverse Leakage Current (Rated V _R , T _A = 150°C, 300 μsec pulse minimum)		I _{R2}	—	2	250	μA
Junction Capacitance (V _R = 10V, f = 1MHz, T _A = 25°C)		C _J	—	150	250	pF

NOTES: * Pulse Test: Pulse Width = 300 μsec, Duty Cycle = 2%

1/ For Ordering Information, Price, and Availability Contact Factory.

2/ For Package Outlines Contact Factory.

3/ Unless Otherwise Specified, All Electrical Characteristics @25°C

Available Part Numbers:


SSR05C100G, SSR05C100GL, SSR05C100S.5

SSR05C120G, SSR05C120GL, SSR05C120S.5


PIN ASSIGNMENT

Package	Pin 1	Pin 2	Pin 3
Cerpack (G)	Anode	Anode	Cathode
SMD.5 (S.5)	Cathode	Anode	Anode
Cerpack Leaded (GL)	Anode	Anode	Cathode


Package Outline: CERPACK



Package Outline: SMD.5



Package Outline: LEADED CERPACK



NOTE: All specifications are subject to change without notification.
SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: SH0030G

DOC