



Screwless Connectors Block Connectors

930-00/ 3

Terminal Block without Release Key, 3 pole, Voltage Rating: 450 V,
Current Rating: 24 A, Cross-Section: 2.5 mm²



Order Info

| | |
|------------------------------------|---------------------------------|
| Reference Number (ref. no.) | 112003 |
| Applications | Lighting, Electrical Appliances |
| PU | 1,000 |
| EAN | 4028012104208 |

Type

| | |
|--------------------------------|------------------------------------|
| Type | Terminal Block without Release Key |
| Number of poles | 3 pole |
| Clamping Units per Pole | 2 |
| Colour | white |
| Cross-Section | 2.5 mm ² |
| Connection Type | screwless |

Technical Data

| | |
|---|---|
| Voltage Rating | 450 V |
| Current Rating | 24 A |
| Insulating Material | PA 6.6 |
| Contact Material | Brass |
| Flammability Rating | V-2 |
| max. Ambient Temperature Operation | 85 °C |
| Stripping Length | 8.0-9.0 mm |
| Internal Core Cross-Section max. | 2.5 mm ² |
| External Core Cross-Section min. | 0.5 mm ² |
| External Core Cross-Section max. | 2.5 mm ² |
| Internal Core Cross-Section min. | 0.5 mm ² |
| Type of Conductor Solid External | yes |
| Type of Conductor Solid Internal | yes |
| Approbation EN60998 | 930_935_937_EN60998_20071001_VDE_40022275_web.pdf |
| Approbation UL | 930_935_19880415_19941222_UL_E63492_1-06_Description_web. |
| Approbation CSA | Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765 |